

AC centrifugal fan

forward-curved, single-intake

with housing (large flange)

G4D200-CL12-15 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	G4D200-CL12-15		
Motor	M4D074-EI		
Phase		3~	3~
Nominal voltage	VAC	400	400
Wiring		Y	Y
Frequency	Hz	50	60
Method of obtaining data		fa	ml
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	1300	1550
Power consumption	W	360	340
Current draw	A	0.66	0.62
Min. back pressure	Pa	0	250
Min. back pressure	in. wg	0	1
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	45	30
Starting current	A	1.7	1.7

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011

		Actual	Req. 2015
01 Overall efficiency η_e	%	37.8	37.8
02 Measurement category		B	
03 Efficiency category		Total	
04 Efficiency grade N		49	49
05 Variable speed drive		No	

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_e	kW	0.17
09 Air flow q_v	m³/h	800
09 Pressure increase p_f	Pa	287
10 Speed (rpm) n	min ⁻¹	1425
11 Specific ratio*		1.00

* Specific ratio = $1 + p_f / 100\,000\text{ Pa}$

LU-105245



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Technical description


Weight	7.4 kg
Size	200 mm
Motor size	74
Rotor surface	Painted black
Impeller material	Sheet steel, galvanized
Housing material	Sheet steel, galvanized
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent as per EN 60034-5
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60034-1; EN 60204-1; EN 60335-1; CE
Approval	UL 1004-1; CSA C22.2 No. 100



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Product drawing




1	Cable PVC 4G 0.75 mm²
	4x splice



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Connection diagram




	Three-phase motor
Y	Star connection
1	Counterclockwise operation
L1	= V1 = blue
L2	= U1 = black
L3	= W1 = brown
2	Clockwise operation
L1	= V1 = black
L2	= U1 = blue
L3	= W1 = brown
PE	green/yellow



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-105245-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	Y	400	50	1300	360	0.66	1670	0	980	0.00
2	Y	400	50	1335	296	0.57	1430	100	840	0.40
3	Y	400	50	1375	247	0.52	1195	180	705	0.72
4	Y	400	50	1420	182	0.47	840	260	495	1.04


Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase



AC centrifugal fan

forward-curved, single-intake
with housing (large flange)

Curves: Air performance 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-105247-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	Y	400	60	1550	340	0.62	1245	250	730	1.00
2	Y	400	60	1580	297	0.52	1105	300	650	1.20
3	Y	400	60	1645	230	0.44	855	350	505	1.41

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

