

EC centrifugal fan combination

forward curved
with housing

K1G146-AC01-01 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	K1G146-AC01-01	
Motor	M1G055-DF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Type of data definition		ml
Speed (rpm)	min ⁻¹	800
Power input	W	50
Current draw	A	0.44
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations




Technical features

Mass	3.2 kg
Size	146 mm
Surface of rotor	Thick layer passivated
Material of electronics housing	PP plastic
Material of impeller	PP plastic
Housing material	PP plastic
Motor suspension	Motor mounted anti-vibration on both sides
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 20
Insulation class	"B"
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None, open rotor
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limit - Soft start - PWM control input - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected motor
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1; CE

EC centrifugal fan combination

forward curved
with housing

Product drawing




1	Connection line PVC AWG20, 3x lead tips crimped
2	Connection line PVC AWG20, 3x lead tips crimped
3	8x sheet metal nut for thread EN ISO 1478-ST4.8 (min. screw length 14.5 mm plus thickness of mounting material)

EC centrifugal fan combination

forward curved

with housing

Connection screen




No.	Conn.	Designation	Colour	Function / assignment
	6	L	black	Power supply 230 VAC, 50-60 Hz, see type plate for voltage range
	5	N	blue	Neutral conductor
	4	PE	green/yellow	Protective earth
	3	Tach	white	Tach output: Open collector, 1 pulse per revolution, electrically isolated, Isink max = 10 mA
	2	PWM	yellow	Control input PWM, electrically isolated, Isink = 5-10 mA
	1	GND	blue	GND connection of control interface



EC centrifugal fan combination

forward curved
with housing

Charts: Air flow 50 Hz



Measurement: LU-166506-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	230	50	800	50	0.44	1205	0	710	0.00
2	230	50	970	50	0.44	1000	40	585	0.16
3	230	50	1210	50	0.44	725	80	425	0.32
4	230	50	1395	50	0.44	555	110	325	0.44

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

