

Nominal data

Type	K1G200-AA95-06		
Motor	M1G055-BD		
Phase		1~	1~
Nominal voltage	VAC	115	115
Frequency	Hz	50/60	50/60
Method of obtaining data		ml	
Speed (rpm)	min ⁻¹	2000	1000
Power consumption	W	31	
Current draw	A	0.5	
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	50	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

EC diagonal module - ESM

sickle-shaped blades (S series), single-intake
with support bracket

Technical description


Weight	1.1 kg
Fan size	200 mm
Rotor surface	Unpainted
Blade material	PA plastic
Support bracket material	PA plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54; only with suitable plug, to be installed by customer
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Speed selection max./min. - ESM+ expandable with plug-in module - Soft start - Thermal overload protection for motor
Speed levels	2
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) internally connected
Protection class	II
Conformity with standards	EN 60335-1; EN 60335-2-24; EN 60335-2-80; EN 60335-2-89; CE
Approval	UL 1004-3; CSA C22.2 No. 77; VDE



EC diagonal module - ESM


sickle-shaped blades (S series), single-intake
with support bracket

Product drawing




- | | |
|---|--|
| 2 | Pin S, speed selection (flat plug 2.8 x 0.5) |
| 3 | Pin L1, phase (flat plug 2.8 x 0.5) |
| 4 | Pin N, neutral conductor (flat plug 2.8 x 0.5) |

Connection diagram



Curves: Air performance 50 Hz



Measurement: LU-123230-1
Measurement: LU-123235-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	115	50	2000	27	0.38	575	0	340	0.00
2	115	50	2000	29	0.42	500	40	295	0.16
3	115	50	2000	31	0.50	415	80	245	0.32
4	115	50	2000	30	0.43	295	120	170	0.48
5	115	50	1000	5.6	0.09	280	0	165	0.00
6	115	50	1000	6.3	0.09	245	10	145	0.04
7	115	50	1000	6.3	0.10	200	19	120	0.08
8	115	50	1000	6.7	0.11	145	29	85	0.12

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase