

K1G220-AF92-09

EC centrifugal module

backward-curved
with support bracket

K1G220-AF92-09 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	K1G220-AF92-09		
Motor	M1G055-BD		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50/60	50/60
Method of obtaining data		ml	
Speed (rpm)	min ⁻¹	1600	1000
Power consumption	W	33	-
Current draw	A	0.25	
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	50	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change




Technical description

Weight	1.5 kg
Fan size	220 mm
Rotor surface	Galvanized
Blade material	PA plastic
Support bracket material	PA plastic
Inlet nozzle material	PA plastic
Number of blades	11
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54; only with suitable plug, to be installed by customer
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Thermal overload protection for motor - Speed selection max./min.
Speed levels	2
EMC immunity to interference	According to EN 61000-6-2
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) internally connected
Protection class	II
Conformity with standards	EN 60335-1; EN 60335-2-24; EN 60335-2-80; EN 60335-2-89; CE
Approval	UL 1004-3; CSA C22.2 No. 77; VDE

EC centrifugal module


backward-curved
with support bracket

Product drawing




- | | |
|---|--|
| 1 | Pin S, speed selection (flat plug 2.8 x 0.5) |
| 2 | Pin L1, phase (flat plug 2.8 x 0.5) |
| 3 | Pin N, neutral conductor (flat plug 2.8 x 0.5) |

Connection diagram



Curves: Air performance 50 Hz



Measurement: LU-116642-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	inH2O
1	230	50	1600	18	0.14	51	59	605	0	355	0.00
2	230	50	1600	25	0.20	50	57	515	50	305	0.20
3	230	50	1600	33	0.25	48	55	390	100	230	0.40
4	230	50	1600	32	0.25	49	56	270	130	160	0.52
5	230	50	1000	4.0	0.03	39	47	375	0	220	0.00
6	230	50	1000	6.0	0.05	37	45	320	19	190	0.08
7	230	50	1000	8.0	0.06	36	43	240	38	140	0.15
8	230	50	1000	8.0	0.06	37	44	165	50	100	0.20

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase