

K3G097-BK34-65

EC dual centrifugal fan

forward-curved, with brushless DC motor
with housing, Automotive



K3G097-BK34-65 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	K3G097-BK34-65	
Motor	M3G074-CF	
Nominal voltage	VDC	26
Nominal voltage range	VDC	16 .. 32
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	4040
Power consumption	W	344
Current draw	A	13.3
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	70

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	43.1	33.9
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		53.2	44
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_e	kW	0.25
09 Air flow q_v	m ³ /h	695
09 Pressure increase p_{fs}	Pa	500
10 Speed (rpm) n	min ⁻¹	4590
11 Specific ratio*		1.01

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-74386



EC dual centrifugal fan

forward-curved, with brushless DC motor
with housing, Automotive

Technical description


Weight	2.2 kg
Size	97 mm
Motor size	74
Impeller material	PA plastic
Housing material	PP plastic
Number of blades	34
Balancing grade according to DIN ISO 1940-1	G 2.5
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	Motor IP24 KM
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+85 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Cooling hole/opening	On rotor side
Mode	S1
Motor bearing	Ball bearing; (sealed)
Life expectancy	40,000 h (typical)
Technical features	- Start at 85 °C (2 min) permitted - Load dump (58 V) - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Overvoltage detection - Thermal overload protection for electronics - Line undervoltage detection
EMC regulations	According to ECE R10 Rev. 3
Electrical hookup	Plug; Standby current less than 500 µA
Motor protection	Passive reverse polarity and locked-rotor protection
Approval	R10; EAC
Sound level	76 dB(A), sound power level according to ISO 13347
Comment	Not approved for continuous operation at maximum back pressure and 85 °C; type approval number – 036432



EC dual centrifugal fan

forward-curved, with brushless DC motor
with housing, Automotive

Product drawing



1 6-pole header TE Junior Power Timer WE_9901118

1.1 + UB

1.2 GND

1.3 PWM/LIN, 100% speed

1.4 80% speed

1.5 60% speed

1.6 not used


Accessory part: Cable (460 mm) with mating connector, part no. 02001-4-1021 not included in scope of delivery
6-pole mating connector TE 929504-2, 4x plug contact TE 927771-1, 2x plug contact TE 927768-1

2 Electronics cover blue (RAL 5015)

EC dual centrifugal fan

forward-curved, with brushless DC motor
with housing, Automotive

Connection diagram




No.	Conn.	Designation	Function/assignment
	1.1	+UB	Power supply
	1.2	GND	Power supply GND, reference ground
	1.3	100%, PWM/LIN	100% speed, analog voltage control input 0-10 V or PWM
	1.4	80%	80% speed
	1.5	60%	60% speed
	1.6	NC	Not used / no function



EC dual centrifugal fan

forward-curved, with brushless DC motor
with housing, Automotive

Curves: Air performance



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-74386-1
Measurement: LU-74387-1
Measurement: LU-74388-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / Sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Stage	U	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	P _{st}	q _v	P _{st}
		V	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	3	26	4040	344	13.30	70	81	1105	0	650	0.00
2	3	26	4275	306	11.81	70	81	930	300	545	1.20
3	3	26	4595	251	9.68	69	80	690	500	405	2.01
4	3	26	4795	218	8.39	69	80	450	600	265	2.41
5	2	26	3305	186	7.18			905	0	530	0.00
6	2	26	3425	158	6.10			740	194	435	0.78
7	2	26	3615	128	4.95			545	306	320	1.23
8	2	26	3735	107	4.12			350	363	205	1.46
9	1	26	2325	67	2.58			635	0	375	0.00
10	1	26	2385	58	2.26			510	90	300	0.36
11	1	26	2455	45	1.72			365	139	215	0.56
12	1	26	2505	38	1.45			230	160	135	0.64

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side · q_v = Air flow
P_{st} = Pressure increase

