

Nominal data


Type	K3G220-RC11-13	
Motor	M3G055-BI	
Phase		1~
Nominal voltage	VAC	115
Nominal voltage range	VAC	100 .. 130
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2330
Power consumption	W	65
Current draw	A	0.95
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Technical description


Weight	2 kg
Fan size	220 mm
Rotor surface	Thick-film passivated
Impeller material	PA plastic
Housing material	PA plastic
Guard grille material	PA plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Tach output - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 0.25 mA
Motor protection	Locked-rotor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	UL 1004-7 + 60730; C22.2 No.77 + CAN/CSA-E60730-1

Product drawing




1	Cable PVC AWG20, 3-pole connector housing Stocko MFMP 9586-003-80D-512-000-00
1.1	L (black)
1.2	N (blue)
1.3	PE (green/yellow)
2	Cable PVC AWG22, 4-pole connector housing Stocko MFMP 7238-004-566-960-000-00-G
2.1	GND (blue)
2.2	0-10 V PWM (yellow)
2.3	+10 V (red)
2.4	Tach (white)
3	Mounting dimensions

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	CON10	L	black	Power supply 115 VAC, 50-60 Hz, see nameplate for voltage range
	CON11	N	blue	Neutral conductor
	CON12	PE	green/yellow	Protective earth
	1	GND	blue	GND connection for control interface
	2	0- 10V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
	3	10V/ max 1.1mA	red	Voltage output 10 VDC 1.1 mA, electrically isolated, short-circuit-proof
	4	Tach	white	Tach output: Open collector, 1 pulse per revolution, electrically isolated, $I_{\text{sink max}} = 10 \text{ mA}$

Curves: Air performance 50 Hz



Measurement: LU-147073-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	inH2O
1	115	50	2565	65	0.95	62	69	925	0	545	0.00
2	115	50	2450	65	0.95	58	66	775	100	455	0.40
3	115	50	2330	65	0.95	55	62	550	200	325	0.80
4	115	50	2430	65	0.95	59	67	280	300	165	1.20
5	115	50	2100	36	0.52	57	64	755	0	445	0.00
6	115	50	2100	41	0.60	54	62	665	74	390	0.30
7	115	50	2100	48	0.69	52	60	495	161	290	0.65
8	115	50	2100	42	0.61	54	62	245	224	145	0.90
9	115	50	1800	23	0.33	53	60	650	0	380	0.00
10	115	50	1800	26	0.38	50	58	570	54	335	0.22
11	115	50	1800	30	0.44	48	56	425	119	250	0.48
12	115	50	1800	26	0.39	50	58	210	164	120	0.66
13	115	50	1500	13	0.19	48	56	540	0	320	0.00
14	115	50	1500	15	0.22	46	53	475	38	280	0.15
15	115	50	1500	17	0.25	43	51	355	82	210	0.33
16	115	50	1500	15	0.22	46	53	175	114	100	0.46

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
 q_v = Air flow · p_{fs} = Pressure increase