

Nominal data

Type	K3G220-RD53-14	
Motor	M3G055-CF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	3230
Power consumption	W	168
Current draw	A	1.4
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	56.6	43.1
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		75.5	62
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_{ed}	kW	0.16
09 Air flow q_v	m ³ /h	805
09 Pressure increase p_{fs}	Pa	366
10 Speed (rpm) n	min ⁻¹	3210
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$


LU-153697



Technical description


Weight	2.1 kg
Fan size	220 mm
Rotor surface	Thick-film passivated
Impeller material	PA plastic
Housing material	PA plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Tach output - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	CCC

Product drawing




1	Cable PVC AWG20, 3-pole connector housing Stocko MFMP 9586-003-80D-512-000-00
1.1	L (black)
1.2	N (blue)
1.3	PE (green/yellow)
2	Cable PVC AWG22, 4-pole connector housing Stocko MFMP 7238-004-566-960-000-00-G
2.1	GND (blue)
2.2	0-10 V PWM (yellow)
2.3	10 V, 1.1 mA (red)
2.4	Tach (white)
3	Mounting dimensions

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	CON10	L	black	Supply connection, power supply, phase, see nameplate for voltage range
	CON11	N	blue	Supply connection, power supply, neutral conductor, see nameplate for voltage range
	CON12	PE	green/yellow	Ground connection
	2	0- 10V PWM	yellow	0-10 V / PWM control input, R _i =100 kΩ, SELV
	4	Tach	white	Tach output, open collector, 1 pulse per revolution, I _{sink} max = 10 mA, SELV
	3	+10 V	red	Fixed voltage output 10 VDC ±3 %, I _{max} . 10 mA, short-circuit-proof, power supply for ext. devices (e.g. pot), SELV
	1	GND	blue	Reference ground for control interface, SELV

Curves: Air performance 50 Hz



Measurement: LU-153697-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	230	50	3540	168	1.40	70	78	1290	0	760	0.00
2	230	50	3370	168	1.40	65	73	1065	200	625	0.80
3	230	50	3230	168	1.40	62	70	750	400	440	1.61
4	230	50	3310	168	1.40	66	74	435	550	255	2.21
5	230	50	3000	99	0.82	66	73	1090	0	645	0.00
6	230	50	3000	115	0.96	62	70	950	159	560	0.64
7	230	50	3000	135	1.12	61	68	700	350	415	1.41
8	230	50	3000	121	1.01	63	70	395	451	230	1.81
9	230	50	2400	51	0.42	60	68	875	0	515	0.00
10	230	50	2400	59	0.49	57	64	760	102	445	0.41
11	230	50	2400	69	0.57	55	63	560	224	330	0.90
12	230	50	2400	62	0.51	57	65	315	289	185	1.16
13	230	50	1800	21	0.18	53	61	655	0	385	0.00
14	230	50	1800	25	0.21	50	57	570	57	335	0.23
15	230	50	1800	29	0.24	48	55	420	126	250	0.51
16	230	50	1800	26	0.22	50	58	235	162	140	0.65

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
 q_v = Air flow · p_{fs} = Pressure increase