

K3G250-RO33-82 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	K3G250-RO33-82	
Motor	M3G084-DF	
Phase		1~
Nominal voltage	VAC	115
Nominal voltage range	VAC	100 .. 130
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	3330
Power consumption	W	375
Current draw	A	4.6
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	55

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



Technical description


Weight	7.9 kg
Size	250 mm
Motor size	84
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PA plastic
Support plate material	Sheet steel, galvanized
Support bracket material	Steel, painted black
Inlet nozzle material	Sheet steel, galvanized
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on top; rotor on bottom on request
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Alarm relay - Motor current limitation - PFC, passive - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Conformity with standards	EN 61800-5-1
Approval	UL 1004-3; EAC; CSA C22.2 No. 77

EC centrifugal module - RadiCal

backward-curved, single-intake

with support bracket

Product drawing




- | | |
|---|--------------------------------------|
| 1 | Cable PVC AWG18, 5x crimped ferrules |
| 2 | Cable PVC AWG22, 3x crimped ferrules |


EC centrifugal module - RadiCal

backward-curved, single-intake
with support bracket

Connection diagram



Curves: Air performance 50 Hz



Measurement: LU-159219-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _V	p _{fs}	q _V	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	115	50	3330	289	3.62	1790	0	1055	0.00
2	115	50	3330	337	4.16	1545	300	910	1.20
3	115	50	3330	375	4.60	1165	600	685	2.41
4	115	50	3330	334	4.13	710	800	415	3.21
5	115	50	2800	172	2.15	1505	0	885	0.00
6	115	50	2800	202	2.49	1305	214	765	0.86
7	115	50	2800	217	2.66	980	426	575	1.71
8	115	50	2800	200	2.48	600	569	350	2.28
9	115	50	2300	95	1.19	1235	0	725	0.00
10	115	50	2300	112	1.38	1070	144	630	0.58
11	115	50	2300	120	1.48	805	287	475	1.15
12	115	50	2300	111	1.37	490	384	290	1.54
13	115	50	1800	46	0.57	965	0	570	0.00
14	115	50	1800	54	0.66	840	88	495	0.35
15	115	50	1800	58	0.71	630	176	370	0.71
16	115	50	1800	53	0.66	385	235	225	0.94

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_V = Air flow · p_{fs} = Pressure increase