

Nominal data

Type	K3G310-AL28-62	
Motor	M3G084-FA	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2110
Power consumption	W	430
Current draw	A	1.9
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	35

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	58.3	47.3
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		73	62
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_{ed}	kW	0.4
09 Air flow q_v	m ³ /h	2005
09 Pressure increase p_{fs}	Pa	384
10 Speed (rpm) n	min ⁻¹	2105
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-122060




Technical description

Weight	7.9 kg
Fan size	310 mm
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	Sheet aluminum
Support plate material	Sheet aluminum
Spacer material	Aluminum
Inlet nozzle material	Sheet aluminum
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP20
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on top; rotor on bottom on request
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - Integrated PID controller - Motor current limitation - PFC, active - RS-485 ebmBUS - Soft start - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	With plug
Motor protection	Thermal overload protector (TOP) internally connected
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1; CE
Approval	UL 1004-3; CSA C22.2 No. 77

EC centrifugal module

backward-curved, single-intake
with support structure

Product drawing




No.	Conn.	Designation	Function/assignment
1			RS485 terminal box
1			Terminal strip WAGO 862-2503
1	1.1	N	Cable AWG18, 1x wire (black 2) with wire-end ferrule
1	1.2	PE	Cable AWG18, 1x wire (green/yellow) with wire-end ferrule
1	1.3	L	Cable AWG18, 1x wire (black 1) with wire-end ferrule
1	1.4	RJ45 Buchse	RSB pin 5 / RSA pin 6
1	1.5	RJ45 Buchse	RSB pin 5 / RSA pin 6



EC centrifugal module

backward-curved, single-intake
with support structure


Connection diagram



No.	Conn.	Designation	Function/assignment
3	PE		Protective earth
2	N		Supply connection, power supply, neutral conductor, voltage range see nameplate, 50/60 Hz
1	L		Supply connection, power supply, phase, voltage range see nameplate, 50/60 Hz
6	RSA		Bus connection RS485, RSA, ebmBUS; SELV
5	RSB		Bus connection RS485, RSB, ebmBUS; SELV



Curves: Air performance 50 Hz



Measurement: LU-122060-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{is}	q _v	p _{is}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	230	50	2165	302	1.32	3170	0	1865	0.00
2	230	50	2135	358	1.56	2645	200	1560	0.80
3	230	50	2110	430	1.90	2000	400	1175	1.61
4	230	50	2135	371	1.63	1195	550	705	2.21
5	230	50	1900	204	0.89	2780	0	1635	0.00
6	230	50	1900	253	1.11	2360	159	1390	0.64
7	230	50	1900	299	1.31	1800	325	1060	1.30
8	230	50	1900	262	1.15	1065	437	625	1.75
9	230	50	1600	122	0.53	2340	0	1380	0.00
10	230	50	1600	151	0.66	1985	113	1170	0.45
11	230	50	1600	178	0.78	1515	231	890	0.93
12	230	50	1600	156	0.69	895	310	525	1.24
13	230	50	1300	65	0.29	1900	0	1120	0.00
14	230	50	1300	81	0.35	1615	74	950	0.30
15	230	50	1300	96	0.42	1230	152	725	0.61
16	230	50	1300	84	0.37	730	204	430	0.82

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{is} = Pressure increase

