

EC centrifugal module - RadiCal

backward-curved, single-intake
with support plate

K3G310-RO38-44 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	K3G310-RO38-44	
Motor	M3G084-DF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2100
Power consumption	W	410
Current draw	A	1.8
Min. ambient temperature	°C	0
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	62.9	47.3
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		77.6	62
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_{ed}	kW	0.4
09 Air flow q_v	m ³ /h	1750
09 Pressure increase p_{fs}	Pa	466
10 Speed (rpm) n	min ⁻¹	2110
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-161250




Technical description

Weight	9.5 kg
Size	310 mm
Motor size	84
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic UL
Support plate material	Sheet aluminum
Spacer material	Aluminum
Inlet nozzle material	Sheet steel, galvanized
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP20
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on top; rotor on bottom on request
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - Integrated PID controller - Motor current limitation - PFC, active - RS485 ebmBUS with DCI function - Soft start - Control interface with SELV potential safely disconnected from supply - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Plug
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1
Approval	CSA C22.2 No. 113; UL 507

EC centrifugal module - RadiCal


backward-curved, single-intake
with support plate

Product drawing



1	Terminal box
2	Connector housing 3-pole GST18/3 Wieland 92.032.9058.0
2.1	N
2.2	PE
2.3	L
3	RJ45 jack (RSA pin 1 + 3 / RSB pin 2 + 6)
4	RJ45 jack (RSA pin 1 + 3 / RSB pin 2 + 6)
5	ARCOELECTRIC SWITCHES P L C (no. H8550VBACF) As-delivered condition end customer switch set to "OFF"

Connection diagram




LED1 / LED2

Status	Priority	Address S/N	Speed	green LED	red LED
Malfunction	1	S/N any	any	off	flashing 1 Hz
Flashing	2	S/N = 1/1	any	flashing 10 Hz	on
Flashing	2	S/N > 1	any	flashing 10 Hz	off
after set value change	3	S/N = 1/1	any	flashing 3 times at 2.5 Hz	on
after set value change	3	S/N > 1	any	flashing 3 times at 2.5 Hz	off
Fan speed 0	4	S/N = 1/1	n = 0	flashing 1 Hz	on
Fan speed 0	4	S/N > 1	n = 0	flashing 1 Hz	off
Fan speed >0	4	S/N = 1/1	n > 0	off	on
Fan speed >0	4	S/N > 1	n > 0	on	off

No.	Conn.	Designation	Function/assignment
KL1	1	L	Power supply, phase, 50/60 Hz
KL1	2	N	Power supply, neutral conductor, 50/60 Hz
KL1	3	PE	Protective earth
KL2/KL3	1	RSA	RS485 interface for ebmbUS, RSA
KL2/KL3	2	RSB	RS485 interface for ebmbUS, RSB
KL2/KL3	3	RSA	RS485 interface for ebmbUS, RSA
KL2/KL3	4	-	Bridge KL2-KL3
KL2/KL3	5	-	Bridge KL2-KL3
KL2/KL3	6	RSB	RS485 interface for ebmbUS, RSB
KL2/KL3	7	GND	Reference ground
KL2/KL3	8	DCI	Daisy chain signal
KL2/KL3	9	Schirm	Shield for RJ45 CAT5 wire (not used)

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-161250-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	1~	230	50	2100	281	1.23	3120	0	1840	0.00
2	1~	230	50	2100	362	1.58	2675	200	1575	0.80
3	1~	230	50	2100	410	1.80	2065	400	1215	1.61
4	1~	230	50	2100	344	1.50	1050	550	620	2.21
5	1~	230	50	1800	174	0.76	2660	0	1565	0.00
6	1~	230	50	1800	222	0.97	2275	145	1340	0.58
7	1~	230	50	1800	254	1.11	1755	290	1035	1.16
8	1~	230	50	1800	212	0.93	895	398	525	1.60
9	1~	230	50	1500	101	0.44	2220	0	1305	0.00
10	1~	230	50	1500	129	0.56	1895	101	1115	0.41
11	1~	230	50	1500	147	0.64	1465	201	860	0.81
12	1~	230	50	1500	123	0.54	745	277	440	1.11
13	1~	230	50	1200	52	0.23	1775	0	1045	0.00
14	1~	230	50	1200	66	0.29	1515	64	890	0.26
15	1~	230	50	1200	75	0.33	1170	129	690	0.52
16	1~	230	50	1200	63	0.27	595	177	350	0.71

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

