

EC centrifugal module - RadiCal

backward-curved, single-intake
with support structure, for rail applications

K3G310-RR12-P1 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	K3G310-RR12-P1	
Motor	M3G084-DF	
Nominal voltage	VDC	110
Nominal voltage range	VDC	77 .. 138
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2260
Power consumption	W	465
Current draw	A	4.2
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	65.9	48
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		79.9	62
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_e	kW	0.46
09 Air flow q_v	m³/h	2105
09 Pressure increase p_{fs}	Pa	472
10 Speed (rpm) n	min ⁻¹	2260
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-160428



EC centrifugal module - RadiCal

backward-curved, single-intake
with support structure, for rail applications

Technical description

Weight	10.5 kg
Size	310 mm
Motor size	84
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PA plastic
Inlet nozzle material	Sheet steel, galvanized
Support structure material	Aluminum
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H3
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing; (sealed)
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display - Alarm relay - Motor current limitation - RS-485 MODBUS-RTU - Soft start - EEPROM write cycles: 100,000 maximum - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
EMC regulations	According to EN 50121-3-2
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 15085-1, CPC3: 2013; EN 45545-2, HL3: 2013 + A1:2015; EN 50155: 2008; EN 61373, Cat. 1B: 2010; CE
Approval	EAC
Comment	If voltage (e.g. 230 VAC) is passed through the alarm relay, the SELV signal wires lose their property of reinforced insulation, meaning they then have only basic insulation The SELV property (reinforced insulation) is not lost when voltages of up to 110 VDC are passed through the alarm relay.




EC centrifugal module - RadiCal

backward-curved, single-intake

with support structure, for rail applications

Product drawing




1	Cable, halogen-free, railway application EN 45545, 4G 1.5 mm ² 4x wire-end ferrule
2	Cable, halogen-free, railway application EN 45545, 7x 0.5 mm ² 7x wire-end ferrule

EC centrifugal module - RadiCal

backward-curved, single-intake

with support structure, for rail applications

Mounting dimensions




EC centrifugal module - RadiCal

backward-curved, single-intake

with support structure, for rail applications

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	-	black	Power supply, GND, voltage range see nameplate
1	5	+	brown	Power supply, voltage range see nameplate
2	6	COM	gray	Status relay, floating status contact, break for failure, contact rating 250 VAC / max. 2 A (AC1) / min. 1 mA / 5 V, basic insulation on supply side and on control interface side
2	7	NC	orange	Status relay, floating status contact, common connection, contact rating 250 VAC / max. 2 A (AC1) / min. 1 mA / 5 V, basic insulation on supply side and on control interface side
2	8	0-10 V	yellow	Analog input 1, set value: 0-10 V, R _i = 100 kΩ, adjustable curve; SELV
2	10	RSB	brown	RS485 interface for MODBUS, RSB; SELV
2	11	RSA	white	RS485 interface for MODBUS, RSA; SELV
2	12	GND	blue	Reference ground for control interface; SELV
2	13	+10 V	red	Fixed voltage output 10 VDC, +10 V ±3%, max. 10 mA, short-circuit-proof power supply for external devices (e.g. pot); SELV

EC centrifugal module - RadiCal

backward-curved, single-intake
with support structure, for rail applications

Curves: Air performance



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-172392-1
Measurement: LU-160428-1
Measurement: LU-172391-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / Sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	n	P _{ed}	I	q _v	p _{ts}	q _v	p _{ts}
		V	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	Y	138	2505	436	3.16	3690	0	2170	0.00
2	Y	138	2440	513	3.71	3185	225	1875	0.90
3	Y	138	2325	513	3.72	2255	473	1325	1.90
4	Y	138	2370	512	3.71	1525	643	900	2.58
5	Y	110	2355	356	3.24	3475	0	2045	0.00
6	Y	110	2295	428	3.89	3010	200	1770	0.80
7	Y	110	2260	465	4.20	2195	450	1290	1.81
8	Y	110	2290	450	4.09	1475	600	870	2.41
9	Y	77	1735	152	1.97	2535	0	1490	0.00
10	Y	77	1705	180	2.34	2210	110	1300	0.44
11	Y	77	1690	198	2.58	1635	249	960	1.00
12	Y	77	1695	191	2.49	1090	328	640	1.32

Wired = Wiring · U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{ts} = Pressure increase

