

Nominal data

Type	K3G400-RP45-62	
Motor	M3G084-FA	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1300
Power consumption	W	330
Current draw	A	1.5
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	64.3	46.3
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		80	62
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_{ed}	kW	0.32
09 Air flow q_v	m ³ /h	2805
09 Pressure increase p_{fs}	Pa	242
10 Speed (rpm) n	min ⁻¹	1270
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-140434




Technical description

Weight	10.2 kg
Fan size	400 mm
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Support plate material	Sheet aluminum
Spacer material	Aluminum
Inlet nozzle material	Sheet aluminum
Guard grille material	Steel, bright-galvanized and blue chromated
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP20
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F0
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on top; rotor on bottom on request
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - Integrated PID controller - Motor current limitation - PFC, active - RS-485 ebmBUS - Soft start - Control interface with SELV potential safely disconnected from supply - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	≤ 3.5 mA
Electrical hookup	With plug
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1; CE
Approval	C22.2 No.77 + CAN/CSA-E60730-1; UL1004-3 +60730

EC centrifugal module

backward-curved, single-intake
with support plate

Product drawing




1	RS485 terminal box
2	Connector housing Wieland GST18/3 (art. no. 92.032.9058.1)
2.1	N
2.2	PE
2.3	L
3	RJ45 jack (RSB pin 5 / RSA pin 6)
4	RJ45 jack (RSB pin 5 / RSA pin 6)

EC centrifugal module

backward-curved, single-intake
with support plate


Connection diagram



No.	Conn.	Designation	Function/assignment
3	PE		Protective earth
2	N		Supply connection, power supply, neutral conductor, voltage range see nameplate, 50/60 Hz
1	L		Supply connection, power supply, phase, voltage range see nameplate, 50/60 Hz
6	RSA		Bus connection RS485, RSA, ebmBUS; SELV
5	RSB		Bus connection RS485, RSB, ebmBUS; SELV



Curves: Air performance 50 Hz



Measurement: LU-142789-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	inH2O
1	230	50	1300	267	1.16	72	78	4130	0	2430	0.00
2	230	50	1300	313	1.37	67	73	3470	140	2040	0.56
3	230	50	1300	330	1.50	59	66	2575	260	1515	1.04
4	230	50	1300	308	1.35	58	67	1695	340	1000	1.36
5	230	50	1100	158	0.69	67	74	3465	0	2040	0.00
6	230	50	1100	199	0.87	63	69	2985	104	1755	0.42
7	230	50	1100	217	0.95	55	63	2245	197	1320	0.79
8	230	50	1100	192	0.84	54	63	1450	249	855	1.00
9	230	50	900	87	0.38	62	69	2835	0	1670	0.00
10	230	50	900	109	0.48	58	64	2445	69	1440	0.28
11	230	50	900	119	0.52	50	58	1835	132	1080	0.53
12	230	50	900	105	0.46	49	58	1185	167	700	0.67
13	230	50	700	41	0.18	56	62	2205	0	1300	0.00
14	230	50	700	51	0.22	52	58	1900	42	1120	0.17
15	230	50	700	56	0.25	44	51	1425	80	840	0.32
16	230	50	700	50	0.22	43	51	925	101	545	0.41

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase

