

K3G630-FA38-03 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	K3G630-FA38-03	
Motor	M3G150-FF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1270
Power consumption	W	2650
Current draw	A	4.1
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment

Subject to change

Occasional start-up at temperatures between -40 °C and -25 °C is permitted. For continuous operation at ambient temperatures below -25 °C (such as refrigeration applications), a fan design with special low-temperature bearings must be used.

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	71.6	55.9	09 Power consumption P_{ed}	kW	2.6
02 Measurement category		A		09 Air flow q_v	m ³ /h	11380
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	559
04 Efficiency grade N		77.7	62	10 Speed (rpm) n	min ⁻¹	1275
05 Variable speed drive		Yes		11 Specific ratio*		1.01

Data obtained at optimum efficiency level.

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$

LU-194325

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).

The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.

The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

Technical description

Weight	46.6 kg
Size	630 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Support plate material	Sheet steel, galvanized
Support bracket material	Steel, painted black
Inlet nozzle material	Sheet steel, galvanized
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	See legend on product drawing
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box


EC centrifugal module - RadiCal

backward-curved, single-intake

with support bracket

Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 61800-5-1; UKCA; CE
Approval	UL 1004-7 + 60730-1; EAC; CSA C22.2 No. 77 + CAN/CSA-E60730-1

Product drawing




- | | |
|---|---|
| 1 | Installed position: shaft horizontal (install support struts only vertically as illustrated) or rotor on bottom |
| 2 | Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm
(The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted) |
| 3 | Tightening torque 1.5 ± 0.2 Nm |
| 4 | Inlet ring with pressure tap (k-factor: 545) |
| 5 | Attachment for inlet ring and FlowGrid (00630-2-2957 not included in scope of delivery) |

EC centrifugal module - RadiCal

backward-curved, single-intake
with support bracket

Connection diagram




No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V / PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Fan modulation level Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

Terminal/plug assignment

configurable option		For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.3		configurable IO functions: normal / inverse		MODBUS Register for IO mode configuration											
						electrical specification											
CON2	configurable IO mode	Din1 (active high): digital input	Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D158 [0]	switch: set value											
						source: sensor value											
						switch: parameter set: #1 / #2											
						switch: control function: heating (pos.) / cooling (neg.)											
IO1	Ain1 0-10V/PWM: analog input Tach out (open collector output) Diagnostics out (open collector output)	Ain1 0-10V/PWM: analog input Tach out (open collector output) Diagnostics out (open collector output)	Ain1 0-10V/PWM: analog input Tach out (open collector output) Diagnostics out (open collector output)	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC Ri = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV U _{max} = 50VDC, I _{max} = 20mA, SELV U _{max} = 50VDC, I _{max} = 20mA, SELV	D158 [2] D158 [5] D158 [6]	switch: fan enable / disable											
						switch: set value source											
						switch: direction of rotation: cw / ccw											
						switch: control function: heating (pos.) / cooling (neg.)											
IO2	Din2 (active high): digital input Ain2 0-10V/PWM: analog input Ain2 4-20mA: analog input	Din2 (active high): digital input Ain2 0-10V/PWM: analog input Ain2 4-20mA: analog input	Din2 (active high): digital input Ain2 0-10V/PWM: analog input Ain2 4-20mA: analog input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC Ri = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV Ri = 125R, characteristic curve parameterizable, SELV	D159 [0] D159 [2] D159 [3]	switch: parameter set: #1 / #2											
						source: sensor value											
						switch: control function: heating (pos.) / cooling (neg.)											
						switch: direction of rotation: cw / ccw											
IO3	Din3 (active high): digital input Din3 (active low): digital input PWMIn3: digital input, idle level high PWMMin3: digital input, idle level low	Din3 (active high): digital input Din3 (active low): digital input PWMIn3: digital input, idle level high PWMMin3: digital input, idle level low	Din3 (active high): digital input Din3 (active low): digital input PWMIn3: digital input, idle level high PWMMin3: digital input, idle level low	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV 40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [0] D15A [1] D15A [7] D15A [8]	switch: fan enable / disable											
						switch: set value source											
						switch: direction of rotation: cw / ccw											
						switch: control function: heating (pos.) / cooling (neg.)											
IO3	Aou3 0-10V: analog output Tacho out (pulses): analog output Diagnostics out (pulses)	Aou3 0-10V: analog output Tacho out (pulses): analog output Diagnostics out (pulses)	Aou3 0-10V: analog output Tacho out (pulses): analog output Diagnostics out (pulses)	function parameterizable, max. 5mA, max output frequency 300Hz, SELV 0-10V max. 5mA, max output frequency 300Hz, SELV 0-10V max. 5mA, max output frequency 300Hz, SELV MODBUS RTU, specification V6.3, SELV	D15A [4] D15A [5] D15A [6]	switch: fan enable / disable											
						switch: set value source											
						switch: direction of rotation: cw / ccw											
						switch: control function: heating (pos.) / cooling (neg.)											
RSA RSB	RS485 bus connection, voltage output alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	RS485 bus connection, voltage output alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	RS485 bus connection, voltage output alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	MODBUS RTU, specification V6.3, SELV	D16E [-]	switch: fan enable / disable											
						switch: set value source											
Vout	voltage output	voltage output	voltage output	voltage parameterizable 3.3...24VDC +/- 5%, P _{max} =800mW, short-circuit-proof, supply for external devices, SELV 15...50VDC	D16E [-]	switch: fan enable / disable											
						switch: set value source											

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-194325-1

Date: 2026-07-22

Nozzle: 63350-2-4013

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	1270	1534	2.45	79	86	88	19155	0	11275	0.00
2	3~	400	50	1270	2194	3.42	74	82	85	16290	250	9590	1.00
3	3~	400	50	1270	2650	4.10	69	77	81	12610	500	7425	2.01
4	3~	400	50	1270	2460	3.81	71	78	83	8575	625	5050	2.51
5	3~	400	50	1150	1123	1.80	76	83	86	17265	0	10160	0.00
6	3~	400	50	1150	1604	2.50	71	79	83	14675	203	8640	0.81
7	3~	400	50	1150	1941	3.00	66	74	79	11365	406	6690	1.63
8	3~	400	50	1150	1797	2.78	68	76	80	7725	507	4545	2.04
9	3~	400	50	950	633	1.01	71	78	81	14260	0	8395	0.00
10	3~	400	50	950	904	1.41	67	74	78	12125	139	7135	0.56
11	3~	400	50	950	1094	1.69	61	69	74	9385	277	5525	1.11
12	3~	400	50	950	1013	1.57	63	71	75	6380	346	3755	1.39
13	3~	400	50	750	312	0.50	65	72	75	11260	0	6625	0.00
14	3~	400	50	750	445	0.69	61	68	72	9570	86	5635	0.35
15	3~	400	50	750	538	0.83	55	63	68	7410	173	4360	0.69
16	3~	400	50	750	498	0.77	57	65	69	5035	216	2965	0.87

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
 LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase