


M6D138-NA03-XA ebmpapst Datasheet
sales@fansco.com
www.fansco.com



Nominal data

Type	M6D138-NA03-XA				
Motor	M6D138-NA				
Phase		3~	3~	3~	3~
Nominal voltage	VAC	230	277	400	480
Connection		Δ	Δ	Y	Y
Frequency	Hz	50	60	50	60
Type of data definition		-	-	-	-
State		prelim.	prelim.	prelim.	prelim.
Valid for approval / standard		CE	CE	CE	CE
Speed	min ⁻¹	-	-	-	-
Power input	W	-	-	-	-
Power output	W	-	-	-	-
Min. ambient temperature	°C	-40	-40	-40	-40
Max. ambient temperature	°C	-	-	-	-


ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations



Technical features


Mass	24.7 kg
Size	138 mm
Surface of rotor	Cast in aluminium
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Any
Condensate discharge holes	On rotor and stator sides
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) brought out
Cable exit	Lateral
Product conforming to standard	EN 60034; EN 61800-5-1

Product drawing



1	Depth of screw max. 18 mm
2	Depth of screw max. 18 mm
3	Connection line silicone, 9x0.75 mm ² , 9x brass lead tips crimped

Connection screen



Changing the direction of rotation by reversing the two phases

Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2 x grey
PE	green / yellow				

