

R3G180-AI17-12 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R3G180-AI17-12	
Motor	M3G055-CF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	3000
Power consumption	W	77
Current draw	A	0.73
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change




Technical description

Weight	2.4 kg
Size	180 mm
Motor size	55
Rotor surface	Thick-film passivated
Terminal box material	PA plastic
Impeller material	Sheet steel, rust- and acid-resistant
Support plate material	Sheet steel, rust- and acid-resistant
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	<ul style="list-style-type: none"> - Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for motor
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Plug
Motor protection	Electronic motor protection
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE




Product drawing



1	3-pole connector housing Wieland 93.032.3357.0
1.1	N (blue)
1.2	PE (green/yellow)
1.3	L (black)
2	3-pole connector housing Wieland 93.031.3257.0
2.1	0-10 V/PWM (yellow)
2.2	GND (blue)
2.3	Tach (white)




Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	CON10	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
	CON11	N	blue	Neutral conductor
	CON12	PE	green/yellow	Protective earth
	1	GND	blue	GND connection for control interface
	2	0- 10V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
	4	Tach	white	Tach output: open collector, 1 pulse per revolution, electrically isolated



Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-156445-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _v	P _{fs}	q _v	P _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	230	50	3000	77	0.73	465	0	275	0.00
2	230	50	2980	77	0.73	385	160	225	0.64
3	230	50	3035	75	0.71	315	280	185	1.12
4	230	50	3100	68	0.65	220	380	130	1.53
5	230	50	2800	64	0.60	435	0	255	0.00
6	230	50	2800	64	0.60	360	141	210	0.57
7	230	50	2800	59	0.55	290	239	170	0.96
8	230	50	2800	50	0.48	200	309	115	1.24
9	230	50	2300	36	0.33	355	0	210	0.00
10	230	50	2300	35	0.33	295	95	175	0.38
11	230	50	2300	32	0.31	240	161	140	0.65
12	230	50	2300	28	0.27	165	209	95	0.84
13	230	50	1800	17	0.16	280	0	165	0.00
14	230	50	1800	17	0.16	230	58	135	0.23
15	230	50	1800	16	0.15	190	99	110	0.40
16	230	50	1800	13	0.13	130	128	75	0.51

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_s = Pressure increase

