

EC centrifugal fan

backward curved



R3G190-AB23-19 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	R3G190-AB23-19	
Motor	M3G055-CF	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50/60
Type of data definition		ml
Speed	min ⁻¹	3350
Power input	W	100
Current draw	A	0.74
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60


ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations




Technical features

Mass	1.3 kg
Size	190 mm
Surface of rotor	Galvanised
Material of electronics housing	Die-cast aluminium
Material of impeller	Plastic PA6, fibreglass-reinforced
Number of blades	7
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 44
Insulation class	"B"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None, open rotor
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Reverse polarity and locked-rotor protection
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1

Product drawing




Connection screen



Line	No.	Signal	Colour	Function / assignment
	2	L	brown	Power supply 230 VAC, 50-60 Hz, see type plate for voltage range
	3	N	blue	Neutral conductor
	1	PE	green/yellow	Protective earth
	7	0-10 V PWM	yellow	Control input 0 - 10 V or PWM, electrically isolated
	5	Tach	white	Tach output: Open Collector, 1 pulse per revolution, electrically isolated
	6	10V / max. 1.1 mA	red	Voltage output 10V / 1.1mA, electrically isolated, not short-circuit-proof
	4	GND	blue	GND - Connection for control interface

Charts: Air flow 50 Hz



Measurement: LU-110198

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	qv	p _{ts}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa
1	230	50	3535	88	0.71	71	78	790	0
2	230	50	3455	97	0.74	67	75	645	160
3	230	50	3350	100	0.74	63	71	465	315
4	230	50	3515	90	0.71	64	72	210	480
5	230	50	2820	45	0.36	66	76	630	0
6	230	50	2820	53	0.41	63	74	530	105
7	230	50	2820	58	0.45	59	70	385	217
8	230	50	2820	47	0.37	59	70	170	310
9	230	50	2265	23	0.19	61	68	505	0
10	230	50	2265	27	0.21	58	66	425	68
11	230	50	2265	30	0.24	54	62	310	140
12	230	50	2265	24	0.19	54	62	135	200
13	230	50	1700	9.8	0.08	55	62	380	0
14	230	50	1700	12	0.09	52	60	320	38
15	230	50	1700	13	0.10	48	56	230	79
16	230	50	1700	10	0.08	48	56	100	113

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · qv = Air flow
p_{ts} = Pressure increase

