

EC centrifugal fan - Plug fan

backward curved, single inlet



R3G450-AQ06-03 ebmpapst Datasheet
sales@fansco.com
www.fansco.com



Nominal data

Type	R3G450-AQ06-03	
Motor	M3G150-FF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Type of data definition		ml
Speed	min ⁻¹	2040
Power input	W	2715
Current draw	A	4.1
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.01

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}	%	65.4	52	56
Efficiency grade N		71.4	58	62
Power input P_{ed}	kW	2.71		
Air flow q_v	m ³ /h	6915		
Pressure increase p_{fs}	Pa	875		
Speed n	min ⁻¹	2050		

Data definition with optimum efficiency. LU-118210
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.




Technical features

Mass	21 kg
Size	450 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Aluminium sheet
Number of blades	7
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F4-1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Output 20 VDC, max. 50 mA - Output for slave 0-10 V - Input for sensor 0-10 V or 4-20 mA - Alarm relay - Integrated PID controller - Motor current limit - PFC, passive - RS485 ebmBUS - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1; CE
Approval	UL 2111; VDE; EAC; CSA C22.2 Nr.77

EC centrifugal fan - Plug fan

backward curved, single inlet

Product drawing



1	Cable diameter: min. 4 mm, max. 10 mm, tightening torque: 4 ± 0.6 Nm
2	Accessory part: inlet nozzle 45075-2-4013 with pressure tap not included in the standard scope of delivery; other inlet nozzles on request
3	Depth of screw max. 25 mm
4	Tightening torque 3.5 ± 0.5 Nm


EC centrifugal fan - Plug fan

backward curved, single inlet


Connection screen

Customer circuit


Full speed





Speed setting



Setting of values, e.g. via pressure



Speed setting via potentiometer




No.	Conn.	Designation	Function / assignment
PE		PE	Protective earth connection
KL1	1, 2, 3	L1, L2, L3	Supply voltage, 50/60 Hz
KL2	1	NC	Floating status message contact, normally closed connection
KL2	2	COM	Floating status message contact, changeover contact, common connection (2 A, max. 250 VAC, min. 10 mA, AC1)
KL2	3	NO	Floating status message contact, normally open connection
KL3	1	OUT	Analog output, 0-10 VDC, max. 3 mA, SELV, output of the current level control coefficient: 1 V equates to 10 % level control coefficient. 10 V equate to 100 % level control coefficient.
KL3	2, 8	GND	Reference mass for control interface, SELV
KL3	3, 7	0-10 V	Use control / actual value input 0-10 VDC, impedance 100 kΩ only as alternative to 4-20 mA input, SELV
KL3	4	+10 V	Voltage output 10 VDC (+/-3 %), max. 10 mA, supply voltage for ext. devices (e.g. potentiometers), SELV
KL3	5	+20 V	Voltage output 20 VDC (+25 %/-10 %), max. 50 mA, supply voltage for ext. devices (e.g. sensors), SELV
KL3	6	4-20 mA	Use control / actual value input 4-20 mA, impedance 100 Ω, only as alternative to 0-10 V input, SELV
KL3	9, 11	RSB	RS485 interface for ebmBus, RSB, SELV
KL3	10, 12	RSA	RS485 interface for ebmBus, RSA, SELV



EC centrifugal fan - Plug fan

backward curved, single inlet

Charts: Air flow 50 Hz



Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{wA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa
1	400	50	2040	1783	2.72	85	93	98	10350	0
2	400	50	2040	2339	3.57	78	85	91	8900	500
3	400	50	2040	2715	4.10	75	81	88	6980	900
4	400	50	2040	2569	3.90	77	84	89	4860	1100
5	400	50	1700	1008	1.54	81	89	94	8560	0
6	400	50	1700	1332	2.03	74	81	87	7380	344
7	400	50	1700	1540	2.35	71	77	84	5785	619
8	400	50	1700	1456	2.21	73	80	85	4020	758
9	400	50	1400	563	0.86	77	84	90	7050	0
10	400	50	1400	744	1.13	70	77	83	6075	233
11	400	50	1400	860	1.32	66	73	80	4765	420
12	400	50	1400	813	1.23	69	75	81	3310	514
13	400	50	1100	273	0.42	72	79	84	5540	0
14	400	50	1100	361	0.55	65	72	78	4775	144
15	400	50	1100	417	0.64	61	68	75	3745	259
16	400	50	1100	394	0.60	63	70	76	2600	317

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · LwA_{out} = Sound power level outlet side
qv = Air flow · p_{fs} = Pressure increase

