

R3G500-AQ12-05 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	R3G500-AQ12-05	
Motor	M3G150-IF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Type of data definition		ml
State		prelim.
Speed	min ⁻¹	2000
Power input	W	4350
Current draw	A	6.7
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	+40

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.01

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}		64.5	54.1	58.1
Efficiency grade N		68.4	58	62
Power input P_{ed}	kW	4.27		
Air flow q_v	m ³ /h	8725		
Pressure increase p_{fs}	Pa	1091		
Speed n	min ⁻¹	2020		


Data established at point of optimum efficiency



Technical features

Mass	33 kg
Size	500 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Aluminium sheet
Number of blades	7
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F5
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- PFC, passive - Control input 0-10 VDC / PWM - Output 10 VDC, max. 10 mA - Over-temperature protected electronics / motor - Alarm relay - Integrated PID controller - Input for sensor 0-10 V or 4-20 mA - Output for slave 0-10 V - Output 20 VDC, max. 50 mA - RS485 ebmBUS - Motor current limit - Soft start - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2
EMC interference emission	Acc. to EN 61000-6-3
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	CE


Product drawing



Screws and balance weights of stainless steel

1	Accessory part: Inlet nozzle 63092-2-4013, not included in the standard scope of delivery
2	Direction of rotation clockwise, seen on rotor
3	Depth of screw max. 20 mm, tightening torque max. 30 Nm
4	Cable diameter: min. 9 mm, max. 16 mm; tightening torque: 6 ± 0.3 Nm
5	Cable diameter: min. 4 mm, max. 10 mm; tightening torque: 4 ± 0.3 Nm
6	Tightening torque 3.5 ± 0.5 Nm

Connection screen




No.	Pin	Signal	Function / assignment
PE		PE	Ground wire
KL1		L3	Power line, L3
KL1		L2	Power line, L2
KL1		L1	Power line, L1
KL2		NC	Alarm relay, normally closed connection
KL2		COM	Alarm relay, COMMON (2 A, 250 VAC, AC1)
KL2		NO	Alarm relay, normally open connection
KL3		+10 V	Supply for external potentiometer, 10 VDC(+/-3 %) max. 10 mA
KL3		Ain1 U	Analogue set value input, 0-10 V (impedance 100 kΩ), can be used as an alternative to connection Ain2 I only
KL3		GND	GND
KL3		RSB	RS485 interface for ebmBus, RS B
KL3		RSA	RS485 interface for ebmBus, RS A
KL3		Aout	Analog output 0-10 V max. 5 mA, output of the current level control coefficient
KL3		Ain2 I	Analogue actual value input, 4-20 mA (impedance 100 Ω), can be used only as an alternative to connection Ain1 U only
KL3		+20 V	Supply for external sensor, 20 VDC (+25 %/-10 %) max. 40 mA
KL3		GND	GND

EC centrifugal fan

backward curved, single inlet

Charts: Air flow 50 Hz



Measurement: LU-109096
Measurement: LU-117418
Measurement: LU-117419

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{wA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	L _{pA_{in}}	L _{wA_{in}}	q _v	p _{ts}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa
1	400	50	2000	2683	4.07	89	98	13600	0
2	400	50	2000	4038	6.15	80	87	10930	822
3	400	50	2000	4271	6.52	77	84	8695	1140
4	400	50	2000	3813	5.79	80	87	5845	1313
5	400	50	1660	1509	2.33	84	92	11250	0
6	400	50	1660	2042	3.13	75	82	8860	538
7	400	50	1660	2233	3.41	73	79	7100	786
8	400	50	1660	2001	3.07	76	82	4780	879
9	400	50	1320	801	1.32	77	85	8960	0
10	400	50	1320	1067	1.71	69	76	7015	337
11	400	50	1320	1134	1.80	67	74	5600	485
12	400	50	1320	1033	1.66	68	75	3795	555

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · L_{pA_{in}} = Sound pressure level inlet side · L_{wA_{in}} = Sound power level inlet side · q_v = Air flow
p_{ts} = Pressure increase

