

EC centrifugal fan

backward curved



R3G630-AB06-08 ebmpapst Datasheet
sales@fansco.com
www.fansco.com



Nominal data

Type	R3G630-AB06-08	
Motor	M3G150-IF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Type of data definition		ml
Speed	min ⁻¹	1200
Power input	W	2800
Current draw	A	4.2
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.01

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}	%	57.9	52.2	56.2
Efficiency grade N		63.7	58	62
Power input P_{ed}	kW	2.81		
Air flow q_v	m ³ /h	10005		
Pressure increase p_{fs}	Pa	555		
Speed n	min ⁻¹	1210		


Data definition with optimum efficiency. LU-109182
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.



Technical features

Mass	29 kg
Size	630 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Sheet aluminium, laser-welded
Number of blades	6
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F4-1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Output 20 VDC, max. 50 mA - Output for slave 0-10 V - Input for sensor 0-10 V or 4-20 mA - Alarm relay - Integrated PID controller - Run monitoring - Motor current limit - PFC, passive - RS485 ebmBUS - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	With plug
Motor protection	Reverse polarity and locked-rotor protection
Cable exit	Lateral
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	CE
Approval	EAC; VDE

Product drawing



Y	View Y
1	Accessory part: inlet nozzle 63070-2-4013 not included in the standard scope of delivery; other inlet nozzles on request
2	Depth of screw max. 25 mm
3	Tightening torque 3.5±0.5 Nm
4	Plug, WAGO No. 0770-0001/K0110174/0000-0300, mating connector (not included in delivery), connection line Ölflex Classic 110 grey 4G2.5 m. GNYE
4.1	Not assigned
4.2	PE
4.3	L1
4.4	L2
4.5	L3
5	Strip, 4-pole contact spacing 5 WAGO No. 231-604, mating connector (not included in delivery), connection line Ölflex Classic 110 grey 4 x 0.75 o. GNYE
5.1	GND
5.2	0 - 10 V / PWM
5.3	COM
5.4	NC


EC centrifugal fan

backward curved

Connection screen


Customer circuit

Speed setting



Connection

Fan / motor




No.	Conn.	Designation	Function / assignment
ST 1	1, 2, 3	L1, L2, L3	Supply voltage, 50/60 Hz
ST 1	4	PE	Protective ground connection
ST 1	5	-	not assigned
ST 2	1	GND	Reference mass for control interface
ST 2	2	0-10 V	Use control / actual value input 0-10 VDC, impedance 100 kOhm only as alternative to 4-20 mA input, SELV
ST 2	3	COM	Floating status message contact, changeover contact, common connection (2 A, max. 250 VAC, min. 10 mA, AC1)
ST 2	4	NC	Floating status message contact and run monitoring, normally closed connection or n<80 rpm



EC centrifugal fan

backward curved

Charts: Air flow 50 Hz



Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	Conn.	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa
1	Y	400	50	1200	2020	3.07	78	85	91	16410	0
2	Y	400	50	1200	2458	3.72	74	82	88	13880	250
3	Y	400	50	1200	2800	4.20	72	79	86	11200	500
4	Y	400	50	1200	2629	3.98	73	81	87	7615	650
5	Y	400	50	1000	1103	1.70	72	79	85	13700	0
6	Y	400	50	1000	1315	2.01	69	76	82	11510	171
7	Y	400	50	1000	1520	2.32	67	74	81	9190	354
8	Y	400	50	1000	1338	2.05	68	75	82	6300	447
9	Y	400	50	750	474	0.82	64	71	77	10280	0
10	Y	400	50	750	554	0.92	61	68	74	8645	96
11	Y	400	50	750	654	1.05	59	67	73	6905	200
12	Y	400	50	750	572	0.94	60	67	74	4735	253
13	Y	400	50	500	161	0.35	53	60	66	6870	0
14	Y	400	50	500	179	0.38	50	57	63	5765	43
15	Y	400	50	500	208	0.43	49	57	63	4620	90
16	Y	400	50	500	188	0.40	49	56	63	3170	113

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
LwA_{out} = Sound power level outlet side · qv = Air flow · p_{fs} = Pressure increase

