

R4D450-AK03-05

AC centrifugal fan

backward-curved, single-intake



R4D450-AK03-05 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R4D450-AK03-05						
Motor	M4D110-GF						
Phase		3~	3~	3~	3~	3~	3~
Nominal voltage	VAC	230	277	400	400	480	480
Wiring		Δ	Δ	Δ	Y	Δ	Y
Frequency	Hz	50	60	50	50	60	60
Method of obtaining data		ml	ml	ml	ml	ml	ml
Status			prelim.				prelim.
Valid for approval/standard		CE	CE	CE	CE	CE	CE
Speed (rpm)	min ⁻¹	1090	1205	1350	1090	1580	1205
Power consumption	W	510	770	730	510	1180	770
Current draw	A	1.52	2.02	1.48	0.88	1.8	1.17
Min. back pressure	Pa	0	0	0	0	0	0
Min. back pressure	inH ₂ O	0	0	0	0	0	0
Min. ambient temperature	°C	-40	-40	-40	-40	-40	-40
Max. ambient temperature	°C	80	55	80	80	55	55
Starting current	A			6.5		7.5	

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change




Technical description

Weight	11.5 kg
Fan size	450 mm
Rotor surface	Cast in aluminum
Terminal box material	ABS plastic, black
Impeller material	Sheet aluminum
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F3-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Via terminal box
Motor protection	Thermal overload protector (TOP) with basic insulation
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1; CE
Approval	CCC; VDE

AC centrifugal fan

backward-curved, single-intake

Product drawing



1	Accessory part: Inlet ring 63045-2-4013 not included in scope of delivery, other inlet rings on request
2	Max. clearance for screw 12 mm
3	Cable diameter: min. 6 mm, max. 12 mm, tightening torque 2 ± 0.3 Nm
4	Tightening torque 1.0 ± 0.15 Nm



AC centrifugal fan

backward-curved, single-intake


Connection diagram



Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2x gray
PE	green/yellow				



Curves: Air performance 50 Hz Δ



Measurement: LU-72617-1
Measurement: LU-72618-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.


Measured values

	Wired	U	f	n	P _e	I	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	inH ₂ O
1	Δ	400	50	1390	564	1.27	6120	0	3600	0.00
2	Δ	400	50	1365	678	1.40	4975	200	2930	0.80
3	Δ	400	50	1350	730	1.48	3520	400	2070	1.61
4	Δ	400	50	1370	648	1.36	2120	500	1250	2.01
5	Y	400	50	1185	426	0.72	5160	0	3040	0.00
6	Y	400	50	1120	483	0.82	4085	135	2405	0.54
7	Y	400	50	1090	510	0.88	2840	261	1670	1.05
8	Y	400	50	1135	469	0.79	1760	344	1035	1.38

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase



Curves: Air performance 60 Hz Δ



Measurement: LU-72619-1
Measurement: LU-121125-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	inH ₂ O
1	Δ	480	60	1635	918	1.49	7195	0	4235	0.00
2	Δ	480	60	1595	1119	1.71	5645	300	3325	1.20
3	Δ	480	60	1580	1180	1.80	4000	550	2355	2.21
4	Δ	480	60	1615	1018	1.59	2205	700	1295	2.81
5	Y	480	60	1370	660	0.92	6015	0	3540	0.00
6	Y	480	60	1290	735	1.05	4555	197	2680	0.79
7	Y	480	60	1205	770	1.17	3195	355	1880	1.43
8	Y	480	60	1320	702	1.00	1830	475	1080	1.91

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

