

AC centrifugal fan

backward curved, single inlet



R4D560-AQ05-06 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	R4D560-AQ05-06		
Motor	M4D138-LA		
Phase		3~	3~
Nominal voltage	VAC	230	400
Connection		Δ	Y
Frequency	Hz	50	50
Type of data definition		ml	ml
Valid for approval / standard		-	-
Speed	min ⁻¹	1340	1340
Power input	W	2320	2320
Current draw	A	7.58	4.38
Min. back pressure	Pa	0	0
Min. ambient temperature	°C	-40	-40
Max. ambient temperature	°C	65	65

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



AC centrifugal fan

backward curved, single inlet

Technical features


Mass	26.5 kg
Size	560 mm
Surface of rotor	Cast in aluminium
Material of impeller	Aluminium sheet
Number of blades	9
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	On rotor and stator sides
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) brought out
Cable exit	Lateral
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60034; EN 61800-5-1
Approval	VDE



AC centrifugal fan


backward curved, single inlet

Product drawing



- | | |
|---|--|
| 1 | Connection line halogen-free, 9 x 0.75 mm ² , 9 x brass lead tips crimped |
| 2 | Accessory part: Inlet nozzle 63071-2-4013, not included in the standard scope of delivery. |
| 3 | Maximum screw depth 18 mm |

Connection screen




Δ	Delta connection	Y	Star connection	L1	black
L2	blue	L3	brown	U1	black
V1	blue	W1	brown	U2	green
V2	white	W2	yellow	TOP	2xgrey
PE	green/yellow				



AC centrifugal fan
backward curved, single inlet

Charts: Air flow 50 Hz Y



Measurement: LU-100339

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	Conn.	U	f	n	P _e	I	LpA _{in}	LwA _{in}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa
1	Y	400	50	1400	1609	3.43	76	85	11560	0
2	Y	400	50	1365	2068	4.01	73	82	9520	300
3	Y	400	50	1340	2320	4.38	71	79	7010	600
4	Y	400	50	1380	1839	3.65	75	83	3500	750

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
qv = Air flow · p_{fs} = Pressure increase

