

R4E400-AN09-09 ebmpapst Datasheet

sales@fansco.com

www.fansco.com



Nominal data

Type	R4E400-AN09-09		
Motor	M4E094-HA		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50	60
Type of data definition		ml	ml
Valid for approval / standard		CE	CE
Speed	min ⁻¹	1370	1500
Power input	W	480	695
Current draw	A	2.4	3.18
Motor capacitor	μF	10	10
Capacitor voltage	VDB	400	400
Min. back pressure	Pa	0	0
Min. ambient temperature	°C	-35	-35
Max. ambient temperature	°C	60	60
Starting current	A	5.92	5

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	No
Specific ratio*	1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}		44.2	44.2	48.2
Efficiency grade N		58	58	62
Power input P_e	kW	0.48		
Air flow q_v	m ³ /h	2400		
Pressure increase p_{fs}	Pa	314		
Speed n	min ⁻¹	1360		

Data established at point of optimum efficiency



AC centrifugal fan

backward curved, single inlet

Technical features


Mass	8.9 kg
Size	400 mm
Surface of rotor	Coated in black
Material of impeller	Aluminium sheet
Number of blades	6
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F5
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing with anti-freezing grease
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) brought out
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60034-1 (2004)



AC centrifugal fan


backward curved, single inlet

Product drawing



- | | |
|---|---|
| 1 | Connection line silicone 6G 0.5 mm ² , 6x brass lead tips crimped |
| 2 | Accessory part: inlet nozzle 54476-2-4013, not included in the standard scope of delivery; other inlet nozzles on request |
| 3 | Depth of screw max. 12 mm |

Connection screen




TOP	2 x grey	U1	blue	Z	brown
U2	black	PE	green / yellow		



AC centrifugal fan

backward curved, single inlet

Charts: Air flow 50 Hz



Measurement: LU-120456

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{wA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values


	U	f	n	P _e	I	L _{pA_{in}}	L _{wA_{in}}	qv	p _{ts}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa
1	230	50	1400	389	1.99	70	79	4120	0
2	230	50	1375	462	2.27	66	75	3490	160
3	230	50	1370	480	2.40	63	72	2470	320
4	230	50	1385	433	2.13	64	73	1400	400

U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · L_{pA_{in}} = Sound pressure level inlet side · L_{wA_{in}} = Sound power level inlet side · qv = Air flow
p_{ts} = Pressure increase



AC centrifugal fan
backward curved, single inlet

Charts: Air flow 60 Hz



Measurement: LU-120458

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{wA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _e	I	L _{pA_{in}}	L _{wA_{in}}	qv	p _{ts}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa
1	230	60	1600	576	2.52	74	83	4690	0
2	230	60	1500	674	3.02	69	78	3800	200
3	230	60	1500	695	3.18	66	75	2635	380
4	230	60	1555	623	2.75	66	75	1595	500

U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · L_{pA_{in}} = Sound pressure level inlet side · L_{wA_{in}} = Sound power level inlet side · qv = Air flow
p_{ts} = Pressure increase

