

Product Data Sheet RG160-28/18NU

ebm**papst**

The engineer's choice



RG160-28/18NU

INDEX

1	General	3
2	Mechanics	3
2.1	General.....	3
2.2	Connections.....	3
3	Operating Data	4
3.1	Electrical Operating Data	4
3.2	Electrical Features	4
3.3	Aerodynamics.....	6
3.4	Sound Data.....	8
4	Environment.....	8
4.1	General.....	8
4.2	Climatic Requirements	8
5	Safety.....	10
5.1	Electrical Safety	10
5.2	Approval Tests.....	10
6	Reliability.....	10
6.1	General.....	10

1 General

Fan type	Blower	
Rotating direction looking at rotor	Counterclockwise	
Airflow direction	Air in axially, Air out radially	
Bearing system	Ball bearing	
Mounting position - shaft	Any	


2 Mechanics

2.1 General

Width	220,0 mm	
Height	220,0 mm	
Depth	56,0 mm	
Mass	1,400 kg	
Housing material	Mixed	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges; Metal flange on mounting plate Screw size	Wire outlet corner: 70 Ncm Remaining corners: 70 Ncm ISO 4762 - M4 degreased, without an additional brace and without washer	

2.2 Connections

Electrical connection	Wires	
Lead wire length	L = 325 mm	
Tolerance	+ - 10 mm	
Tube length	S = 20 mm	
Tolerance	+ - 10 mm	



Wire	Color	Operation	Wire size	Insulation diameter
1	red	+ UB	AWG 22	1,70 mm
2	black	- GND	AWG 22	1,70 mm

3 Operating Data

3.1 Electrical Operating Data

Measurement conditions: Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.

$\Delta p = 0$: corresp. to free air flow (see chapter aerodynamics)
I: corresp. to arithm. mean current value

Note:


No inrush current at U_{nom} means:

The internal electrolytic capacitor 39uF/100V has no resistor or inrush current limitation, essentially the power supply and the type and length of the connecting cable is limiting the Inrush current.

Features	Condition	Symbol	Values		
Voltage range		U	28 V		60,0 V
Nominal voltage		U_N		48,0 V	
Power consumption	$\Delta p = 0$	P	6,6 W	19 W	27 W
Tolerance	0010		+/- 17,5 %	+/- 15,0 %	+/- 17,5 %
Current consumption	$\Delta p = 0$	I	235 mA	395 mA	500 mA
Tolerance	0010		+/- 17,5 %	+/- 15,0 %	+/- 17,5 %
Speed	$\Delta p = 0$	n	1.850 1/min	2.850 1/min	3.350 1/min
Tolerance	0010		+/- 12,5 %	+/- 7,5 %	+/- 10,0 %
Starting current consumption				1.500 mA	

3.2 Electrical Features

Electronic function	None	
Reversed polarity protection	Rectifying diode	
Max. residual current at U_N	$I_F \leq 10$ mA	
Locked rotor protection	Auto restart	
Locked rotor current at U_N	I_{block} approx. 1.500 mA	
Clock signal at locked rotor	t_3 / t_4 typical: 2,6 s / 6,3 s	



3.3 Aerodynamics

Measurement conditions:

Measured with a double chamber intake rig acc. to DIN EN ISO 5801.

Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C;


In the intake and outlet area should not be any solid obstruction within 0,5 m. Motor shaft horizontal.

The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

a.) Operation condition:

2.850 1/min at free air flow

Max. free-air flow ($\Delta p = 0 / \dot{V} = \max.$)	209,0 m ³ /h	
Max. static pressure ($\Delta p = \max. / \dot{V} = 0$)	460 Pa	



3.4 Sound Data

Measurement conditions: Sound pressure level: 1 meter distance between microphone and the air intake.
 Sound power level: Acc. to DIN 45635 part 38 (ISO 10302)
 Measured in a semianchoic chamber with a background noise level of $L_p(A) < 5 \text{ dB(A)}$
 For further measurement conditions see chapter aerodynamics.

a.) Operation condition:

2.850 1/min at free air flow		
Optimal operating point	120,0 m ³ /h @ 166 Pa	
Sound power level at the optimal operating point	6,7 bel(A)	
Sound pressure level at free air flow, measured in rubber bands		

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	70 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic Requirements

IP-protection type (certified)	IP 68 (for fan only, not for connector if applicable) **)	
Humidity requirements	humid temperature, cyclic; according to DIN EN 60068-2-38, 10 cycle and condensation water check; according to DIN EN ISO 6270-2, 14 days	
Salt fog requirements	None	

Permitted application area:

The product is for the use in partial sheltered rooms or open, roofed areas. Direct exposure to water is allowed provided that this does not prevent the normal operation. Saline ambient conditions must be avoided.

Pollution degree 3 (according DIN EN 60664-1)

It occurs conductive pollution or dry non-conductive pollution which becomes conductive due to condensation.

**) The specification of the IP protection refers to the conditions mentioned in certification of the fan. The above mentioned short description of the protection scope is not final. For detailed information of the respective protection scope and definitions, see certification as well as DIN EN 60529 (protection by housings) and ISO 20653 (for vehicles) with the letter K.

Short description of the IP-protection type:

Solid particle Protection: Dust tight.

Protection against deliberate contact: Protected against contact to hazardous parts with a wire.

Protection against water: The fan test according to IP68 (Based on IEC 60529), is conducted in non-operating mode. The fan is tested by a complete immersion in water for a period of 2h at a water-level of 1,2m. Electrical connections are not immersed since they are customer specific.

Please require severity levels and specification parameters from the responsible development departments.

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min. 850 VDC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Clearance / creepage distance	1,0 mm / 1,5 mm	
Protection class	III	



5.2 Approval Tests

CE	EC Declaration of Conformity	Yes
EAC	Eurasian Conformity	Yes
UL	Underwriters Laboratories	Yes / UL audited by CSA according to UL507, Electric Fans
VDE	Association for Electrical, Electronic and Information Technologies	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Canadian Standards Association	Yes / C22.2 No. 113 Fans and Ventilators
CCC	China Compulsory Certification	Yes / GB 12350 Safety Requirements for small Power Motors


6 Reliability

6.1 General

Life expectancy L10 at TU = 40 °C	70.000 h	
Life expectancy L10 at TU max.	35.000 h	
Life expectancy L10 acc. to IPC 9591 at TU = 40 °C	117.500 h	



*) Öffnung f. Montagewand ≥ 115
*) Opening for mounting plate ≥ 115



S&P Rating: 2+ 	Asset & Group No. 	MACRS System: Regs. 263A, 263C, 263D, 263E, 263F, 263G, 263H, 263I, 263J, 263K, 263L, 263M, 263N, 263O, 263P, 263Q, 263R, 263S, 263T, 263U, 263V, 263W, 263X, 263Y, 263Z, 263AA, 263AB, 263AC, 263AD, 263AE, 263AF, 263AG, 263AH, 263AI, 263AJ, 263AK, 263AL, 263AM, 263AN, 263AO, 263AP, 263AQ, 263AR, 263AS, 263AT, 263AU, 263AV, 263AW, 263AX, 263AY, 263AZ, 263BA, 263BB, 263BC, 263BD, 263BE, 263BF, 263BG, 263BH, 263BI, 263BJ, 263BK, 263BL, 263BM, 263BN, 263BO, 263BP, 263BQ, 263BR, 263BS, 263BT, 263BU, 263BV, 263BW, 263BX, 263BY, 263BZ, 263CA, 263CB, 263CC, 263CD, 263CE, 263CF, 263CG, 263CH, 263CI, 263CJ, 263CK, 263CL, 263CM, 263CN, 263CO, 263CP, 263CQ, 263CR, 263CS, 263CT, 263CU, 263CV, 263CW, 263CX, 263CY, 263CZ, 263DA, 263DB, 263DC, 263DD, 263DE, 263DF, 263DG, 263DH, 263DI, 263DJ, 263DK, 263DL, 263DM, 263DN, 263DO, 263DP, 263DQ, 263DR, 263DS, 263DT, 263DU, 263DV, 263DW, 263DX, 263DY, 263DZ, 263EA, 263EB, 263EC, 263ED, 263EE, 263EF, 263EG, 263EH, 263EI, 263EJ, 263EK, 263EL, 263EM, 263EN, 263EO, 263EP, 263EQ, 263ER, 263ES, 263ET, 263EU, 263EV, 263EW, 263EX, 263EY, 263EZ, 263FA, 263FB, 263FC, 263FD, 263FE, 263FF, 263FG, 263FH, 263FI, 263FJ, 263FK, 263FL, 263FM, 263FN, 263FO, 263FP, 263FQ, 263FR, 263FS, 263FT, 263FU, 263FV, 263FW, 263FX, 263FY, 263FZ, 263GA, 263GB, 263GC, 263GD, 263GE, 263GF, 263GG, 263GH, 263GI, 263GJ, 263GK, 263GL, 263GM, 263GN, 263GO, 263GP, 263GQ, 263GR, 263GS, 263GT, 263GU, 263GV, 263GW, 263GX, 263GY, 263GZ, 263HA, 263HB, 263HC, 263HD, 263HE, 263HF, 263HG, 263HH, 263HI, 263HJ, 263HK, 263HL, 263HM, 263HN, 263HO, 263HP, 263HQ, 263HR, 263HS, 263HT, 263HU, 263HV, 263HW, 263HX, 263HY, 263HZ, 263IA, 263IB, 263IC, 263ID, 263IE, 263IF, 263IG, 263IH, 263II, 263IJ, 263IK, 263IL, 263IM, 263IN, 263IO, 263IP, 263IQ, 263IR, 263IS, 263IT, 263IU, 263IV, 263IW, 263IX, 263IY, 263IZ, 263JA, 263JB, 263JC, 263JD, 263JE, 263JF, 263JG, 263JH, 263JI, 263JJ, 263JK, 263JL, 263JM, 263JN, 263JO, 263JP, 263JQ, 263JR, 263JS, 263JT, 263JU, 263JV, 263JW, 263JX, 263JY, 263JZ, 263KA, 263KB, 263KC, 263KD, 263KE, 263KF, 263KG, 263KH, 263KI, 263KJ, 263KK, 263KL, 263KM, 263KN, 263KO, 263KP, 263KQ, 263KR, 263KS, 263KT, 263KU, 263KV, 263KW, 263KX, 263KY, 263KZ, 263LA, 263LB, 263LC, 263LD, 263LE, 263LF, 263LG, 263LH, 263LI, 263LJ, 263LK, 263LL, 263LM, 263LN, 263LO, 263LP, 263LQ, 263LR, 263LS, 263LT, 263LU, 263LV, 263LW, 263LX, 263LY, 263LZ, 263MA, 263MB, 263MC, 263MD, 263ME, 263MF, 263MG, 263MH, 263MI, 263MJ, 263MK, 263ML, 263MN, 263MO, 263MP, 263MQ, 263MR, 263MS, 263MT, 263MU, 263MV, 263MW, 263MX, 263MY, 263MZ, 263NA, 263NB, 263NC, 263ND, 263NE, 263NF, 263NG, 263NH, 263NI, 263NJ, 263NK, 263NL, 263NM, 263NN, 263NO, 263NP, 263NQ, 263NR, 263NS, 263NT, 263NU, 263NV, 263NW, 263NX, 263NY, 263NZ, 263OA, 263OB, 263OC, 263OD, 263OE, 263OF, 263OG, 263OH, 263OI, 263OJ, 263OK, 263OL, 263OM, 263ON, 263OO, 263OP, 263OQ, 263OR, 263OS, 263OT, 263OU, 263OV, 263OW, 263OX, 263OY, 263OZ, 263PA, 263PB, 263PC, 263PD, 263PE, 263PF, 263PG, 263PH, 263PI, 263PJ, 263PK, 263PL, 263PM, 263PN, 263PO, 263PP, 263PQ, 263PR, 263PS, 263PT, 263PU, 263PV, 263PW, 263PX, 263PY, 263PZ, 263QA, 263QB, 263QC, 263QD, 263QE, 263QF, 263QG, 263QH, 263QI, 263QJ, 263QK, 263QL, 263QM, 263QN, 263QO, 263QP, 263QQ, 263QR, 263QS, 263QT, 263QU, 263QV, 263QW, 263QX, 263QY, 263QZ, 263RA, 263RB, 263RC, 263RD, 263RE, 263RF, 263RG, 263RH, 263RI, 263RJ, 263RK, 263RL, 263RM, 263RN, 263RO, 263RP, 263RQ, 263RR, 263RS, 263RT, 263RU, 263RV, 263RW, 263RX, 263RY, 263RZ, 263SA, 263SB, 263SC, 263SD, 263SE, 263SF, 263SG, 263SH, 263SI, 263SJ, 263SK, 263SL, 263SM, 263SN, 263SO, 263SP, 263SQ, 263SR, 263SS, 263ST, 263SU, 263SV, 263SW, 263SX, 263SY, 263SZ, 263TA, 263TB, 263TC, 263TD, 263TE, 263TF, 263TG, 263TH, 263TI, 263TJ, 263TK, 263TL, 263TM, 263TN, 263TO, 263TP, 263TQ, 263TR, 263TS, 263TT, 263TU, 263TV, 263TW, 263TX, 263TY, 263TZ, 263UA, 263UB, 263UC, 263UD, 263UE, 263UF, 263UG, 263UH, 263UI, 263UJ, 263UK, 263UL, 263UM, 263UN, 263UO, 263UP, 263UQ, 263UR, 263US, 263UT, 263UU, 263UV, 263UW, 263UX, 263UY, 263UZ, 263VA, 263VB, 263VC, 263VD, 263VE, 263VF, 263VG, 263VH, 263VI, 263VJ, 263VK, 263VL, 263VM, 263VN, 263VO, 263VP, 263VQ, 263VR, 263VS, 263VT, 263VU, 263VV, 263VW, 263VX, 263VY, 263VZ, 263WA, 263WB, 263WC, 263WD, 263WE, 263WF, 263WG, 263WH, 263WI, 263WJ, 263WK, 263WL, 263WM, 263WN, 263WO, 263WP, 263WQ, 263WR, 263WS, 263WT, 263WU, 263WV, 263WW, 263WX, 263WY, 263WZ, 263XA, 263XB, 263XC, 263XD, 263XE, 263XF, 263XG, 263XH, 263XI, 263XJ, 263XK, 263XL, 263XM, 263XN, 263XO, 263XP, 263XQ, 263XR, 263XS, 263XT, 263XU, 263XV, 263XW, 263XX, 263XY,
---	--	---