

EC axial fan

sickle-shaped blades (S series)

with guard grille for full nozzle

S1G200-BI77-52 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	S1G200-BI77-52	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Frequency	Hz	-
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	2950
Power consumption	W	55
Current draw	A	2.6
Max. back pressure	Pa	120
Max. back pressure	inH ₂ O	0.48
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment

Subject to change



EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle

Technical description


Weight	1.6 kg
Fan size	200 mm
Rotor surface	Painted black
Blade material	Sheet steel, painted black
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	9
Airflow direction	"A"
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP42
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F0
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM
Motor protection	Reverse polarity and locked-rotor protection
With cable	Lateral
Conformity with standards	EN 60950-1
Approval	UL 1004-1; CSA C22.2 No. 77; EAC



EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle

Product drawing




1	Direction of air flow "A"
2	Cable PVC AWG20, 4x crimped splices



EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle


Connection diagram



No.	Conn.	Designation	Color	Function/assignment
1	1	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5 %
1	2	0-10 VDC	yellow	Control input Re > 100k
1	3	Tach	white	Tach output, 3 pulses per revolution, Isink max = 10 mA
1	4	GND	blue	Reference ground



Curves: Air performance



Measurement: LU-48037-1
 Measurement: LU-48036-1
 Measurement: LU-48038-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	cfm	inH ₂ O
1	28	3285	73	2.91	1205	0	710	0.00
2	28	3190	76	3.01	1115	38	655	0.15
3	28	3095	78	3.10	1005	72	590	0.29
4	28	3065	82	3.26	815	110	480	0.44
5	24	2950	55	2.60	1095	0	645	0.00
6	24	2915	57	2.67	1015	30	595	0.12
7	24	2860	60	2.76	915	60	540	0.24
8	24	2785	62	2.88	740	90	435	0.36
9	16	2285	28	2.08	835	0	490	0.00
10	16	2245	28	2.09	770	18	455	0.07
11	16	2200	29	2.13	700	35	410	0.14
12	16	2145	30	2.18	565	53	335	0.21

U = Power supply · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

