

S1G200-CA91-20 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	S1G200-CA91-20		
Motor	M1G055-BD		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50/60	50/60
Type of data definition		ml	ml
Speed (rpm)	min ⁻¹	1800	1500
Power input	W	24	20
Current draw	A	0.2	0.16
Max. back pressure	Pa	40	21
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	60	60

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations




Technical features

Mass	1 kg
Size	200 mm
Material of impeller	PA plastic
Material of guard grille	Plastic, epylen GT50
Number of blades	5
Direction of air flow	"A"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity (F)/environmental protection class (H)	H1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Speed selection max/min - Soft start - Over-temperature protected motor
Speed steps	2
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	II
Product conforming to standard	EN 60335-1; CE
Approval	CSA C22.2 No.77; UL 1004-3; VDE

EC axial fan


sickled blades (S series)
ESM guard grille

Product drawing



- 1 Direction of airflow "A"
- 2 Connection line AWG20; 3x lead tips crimped


Connection screen



EC axial fan

sickled blades (S series)
ESM guard grille

Charts: Air flow 50 Hz



Measurement: LU-156775-1
Measurement: LU-156817-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	230	50	1800	22	0.19	640	0	375	0.00
2	230	50	1800	23	0.20	575	15	340	0.06
3	230	50	1800	24	0.20	490	30	290	0.12
4	230	50	1800	24	0.20	400	40	235	0.16
5	230	50	1500	15	0.14	535	0	315	0.00
6	230	50	1500	18	0.15	480	11	285	0.04
7	230	50	1500	20	0.16	415	21	245	0.08
8	230	50	1500	18	0.15	340	29	200	0.12

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

