

EC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

S1G250-AI37-47 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	S1G250-AI37-47	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	2750
Power consumption	W	105
Current draw	A	5.0
Max. back pressure	Pa	140
Max. back pressure	in. wg	0.56
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Technical description


Weight	2.2 kg
Size	250 mm
Motor size	74
Rotor surface	Painted black
Blade material	Sheet steel, painted black
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	9
Airflow direction	A
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP42
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F0; H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM
Motor protection	Reverse polarity and locked-rotor protection
With cable	Lateral
Conformity with standards	EN 60950-1
Approval	UL 1004-1; CSA C22.2 No. 77



EC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Product drawing




1	Direction of air flow "A"
2	Cable PVC AWG20
	4x splice



EC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
1	1	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5 %
1	2	0-10 VDC	yellow	Control input Re > 100k
1	3	Tach	white	Tach output, 3 pulses per revolution, Isink max = 10 mA
1	4	GND	blue	Reference ground



EC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Curves: Air performance



Measurement: LU-54187-1
Measurement: LU-54186-1
Measurement: LU-54185-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	28	2905	125	5.31	2045	0	1205	0.00
2	28	2785	128	5.51	1840	46	1080	0.18
3	28	2660	131	5.76	1575	91	925	0.37
4	28	2580	134	5.93	1100	136	645	0.55
5	24	2750	105	5.00	1920	0	1130	0.00
6	24	2615	106	5.11	1725	40	1015	0.16
7	24	2510	108	5.29	1475	80	870	0.32
8	24	2420	110	5.47	1035	120	610	0.48
9	16	2180	53	3.74	1520	0	895	0.00
10	16	2120	56	3.91	1370	25	805	0.10
11	16	2050	59	4.12	1195	52	700	0.21
12	16	1995	61	4.29	845	80	500	0.32

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

