

EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle

S1G250-BH37-52 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	S1G250-BH37-52	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	2750
Power consumption	W	105
Current draw	A	5.0
Max. back pressure	Pa	120
Max. back pressure	in. wg	0.48
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle

Technical description


Weight	1.6 kg
Size	250 mm
Motor size	74
Electronics housing material	Rotor: painted black
Impeller material	Sheet steel, painted black
Number of blades	7
Airflow direction	V
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP42
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Installation position	Any
Mode	Continuous operation (S1)
Motor bearing	Ball bearing
Technical features	Control input 0-10 VDC / PWM, tach output, polarity reversal protection, locked-rotor protection
Motor protection	Reverse polarity and locked-rotor protection
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Approval	CSA C22.2 No. 77; EAC; UL 1004-1



EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle

Product drawing




1	Airflow direction "V"
2	Cable PVC AWG20
	4x splice



EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
1	1	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5 %
1	2	0-10 VDC	yellow	Control input Re > 100k
1	3	Tach	white	Tach output, 3 pulses per revolution, Isink max = 10 mA
1	4	GND	blue	Reference ground



EC axial fan

sickle-shaped blades (S series)
with guard grille for full nozzle

Curves: Air performance



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-54187-1
Measurement: LU-54186-1
Measurement: LU-54185-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / Sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _V	p _{fs}	q _V	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	28	2905	125	5.31	2045	0	1205	0.00
2	28	2780	128	5.52	1830	46	1075	0.18
3	28	2650	131	5.78	1545	91	910	0.37
4	28	2585	134	5.92	1025	135	600	0.54
5	24	2750	105	5.00	1910	0	1125	0.00
6	24	2610	106	5.12	1715	40	1010	0.16
7	24	2500	108	5.31	1450	80	855	0.32
8	24	2435	110	5.44	960	120	565	0.48
9	16	2180	53	3.74	1520	0	895	0.00
10	16	2115	56	3.92	1365	25	805	0.10
11	16	2040	59	4.13	1175	53	690	0.21
12	16	2000	61	4.26	785	79	465	0.32

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_V = Air flow · p_{fs} = Pressure increase

