

# EC axial fan - ESM

sickled blades (S series)

with guard grille for full nozzle

S1G300-BB19-11 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen  
County court Stuttgart · HRA 590344

General partner: Elektrobau Mulfingen GmbH · Headquarters Mulfingen  
County court Stuttgart · HRB 590142

## Nominal data

<b>Type</b>	<b>S1G300-BB19-11</b>		
<b>Motor</b>	<b>M1G055-BI</b>		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50/60	50/60
Type of data definition		ml	-
Speed	min <sup>-1</sup>	1300	800
Power input	W	35	-
Current draw	A	0.27	
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	50	50

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit  
Subject to alterations



sickled blades (S series)

with guard grille for full nozzle

### Technical features


Mass	1.8 kg
Size	300 mm
Material of electronics housing	Die-cast aluminium
Material of impeller	Plastic PA6, fibreglass-reinforced
Material of guard grille	Steel, phosphated and coated in black plastic
Number of blades	5
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 70 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing with anti-freezing grease
Technical features	- Speed selection max/min - Soft start - Over-temperature protected motor
Speed steps	2
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
EMC harmonics	Acc. to EN 61000-3-2/3
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	II
Product conforming to standard	EN 60335-1; CE



# EC axial fan - ESM


sickled blades (S series)  
with guard grille for full nozzle

## Product drawing




- 1 Direction of air flow "V"
- 2 Connection line AWG20, 3 x brass lead tips crimped

## Connection screen



## Charts: Air flow 50 Hz



Measurement: LU-110298

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebmpapst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

	U	f	n	P <sub>ed</sub>	I	LpA <sub>in</sub>	LwA <sub>in</sub>	qv	p <sub>fs</sub>
	V	Hz	min <sup>-1</sup>	W	A	dB(A)	dB(A)	m <sup>3</sup> /h	Pa
1	230	50	1300	32	0.25	52	58	1405	0
2	230	50	1300	34	0.27	52	58	1255	15
3	230	50	1300	34	0.27	51	57	1070	28
4	230	50	1300	35	0.27	53	59	900	36
5	230	50	800	9.2	0.09	41	48	820	0
6	230	50	800	10	0.09	40	47	755	6
7	230	50	800	11	0.10	40	47	665	11
8	230	50	800	11	0.11	41	48	565	14

