

EC axial fan

sickle-shaped blades (S series)

ESM guard grille

S1G300-CA19-16 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	VNA0300XSLDZ		
Motor	M1G055-BI		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz		50/60
Method of obtaining data			ml/ce
Speed (rpm)	min ⁻¹	900	1250
Power consumption	W		35
Current draw	A		0.27
Max. back pressure	Pa		40
Max. back pressure	in. wg		0.16
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	50	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan

sickle-shaped blades (S series)

ESM guard grille

Technical description

Weight	1.4 kg
Size	300 mm
Motor size	55
Rotor surface	Cast in PA plastic
Blade material	PA plastic
Guard grille material	PP plastic
Number of blades	5
Airflow direction	A
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1+
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Speed setting input (230 V) - Soft start - Thermal overload protection for motor
Speed levels	2
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Lateral
Protection class	II
Conformity with standards	EN 60034-1; EN 60204-1; CE
Approval	VDE; CSA C22.2 No. 77; UL 1004-3




EC axial fan

sickle-shaped blades (S series)

ESM guard grille

Product drawing



1 Direction of air flow "A"

2 Cable AWG20


3x splice



EC axial fan

sickle-shaped blades (S series)
ESM guard grille


Connection diagram



EC axial fan

sickle-shaped blades (S series)
ESM guard grille

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-186011-1
Measurement: LU-186098-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Stage	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
			V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	2	1~	230	50	1250	27	0.23	56	65	1175	0	695	0.00
2	2	1~	230	50	1250	31	0.26	55	64	1045	15	615	0.06
3	2	1~	230	50	1250	34	0.27	56	65	875	30	515	0.12
4	2	1~	230	50	1250	35	0.27	60	69	650	40	380	0.16
5	1	1~	230	50	900	13	0.13	47	56	825	0	485	0.00
6	1	1~	230	50	900	14	0.15	46	55	730	7	430	0.03
7	1	1~	230	50	900	16	0.16	45	54	610	15	360	0.06
8	1	1~	230	50	900	19	0.19	48	56	470	21	280	0.08

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase

