

EC axial fan - HyBlade

sickle-shaped blades (S series)

with guard grille for full nozzle

S3G300-BH13-10 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	S3G300-BH13-10	
Motor	M3G055-CF	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50/60
Method of obtaining data		me
Speed (rpm)	min ⁻¹	1640
Power consumption	W	77
Current draw	A	0.63
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan - HyBlade

sickle-shaped blades (S series)

with guard grille for full nozzle

Technical description

Weight	2.1 kg
Fan size	300 mm
Rotor surface	Cast in PA plastic
Blade material	PA plastic, black
Guard grille material	Steel, phosphated and coated with black plastic
Number of blades	5
Airflow direction	"V"
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP54; installation- and position-dependent
Insulation class	"B"
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Motor current limitation - Soft start - Thermal overload protection for motor
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1




EC axial fan - HyBlade

sickle-shaped blades (S series)

with guard grille for full nozzle

Product drawing




- | | |
|---|----------------------------------|
| 1 | Direction of air flow "V" |
| 2 | Cable AWG 22, 3x crimped splices |



EC axial fan - HyBlade

sickle-shaped blades (S series)
with guard grille for full nozzle


Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	1	PE	green/yellow	Protective earth
	2	N	blue	Neutral conductor
	3	L	brown	Power supply 230 VAC, 50 - 60 Hz, see nameplate for voltage range



Curves: Air performance 50 Hz



Measurement: LU-126946-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	qv	p _{ts}	qv	p _{ts}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH ₂ O
1	230	50	1760	59	0.49	2110	0	1240	0.00
2	230	50	1710	66	0.54	1875	30	1105	0.12
3	230	50	1675	73	0.60	1595	60	940	0.24
4	230	50	1640	77	0.63	1245	90	735	0.36
5	230	50	1300	24	0.20	1555	0	915	0.00
6	230	50	1300	29	0.24	1425	17	840	0.07
7	230	50	1300	34	0.28	1240	36	730	0.14
8	230	50	1300	38	0.31	985	57	580	0.23
9	230	50	1000	11	0.09	1195	0	705	0.00
10	230	50	1000	13	0.11	1095	10	645	0.04
11	230	50	1000	16	0.13	955	22	560	0.09
12	230	50	1000	17	0.14	760	34	445	0.14

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · qv = Air flow · p_{ts} = Pressure increase

