

EC axial fan

sickled blades (S series)
with guard grille for full nozzle

S3G315-BM01-33 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	S3G315-BM01-33	
Motor	M3G074-CF	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50/60
Type of data definition		ml
Speed (rpm)	min ⁻¹	1635
Power input	W	140
Current draw	A	1.1
Max. back pressure	Pa	120
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

		Actual	Request 2015
01 Overall efficiency η_{es}	%	41.5	28.1
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		53.4	40
05 Variable speed drive		Yes	

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

09 Power input P_{ed}	kW	0.13
09 Air flow q_v	m³/h	1605
09 Pressure increase p_{fs}	Pa	107
10 Speed (rpm) n	min ⁻¹	1650
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-161584




Technical features

Mass	3.9 kg
Size	315 mm
Surface of rotor	Thick layer passivated
Material of electronics housing	Die-cast aluminium
Material of blades	Press-fitted sheet steel blank, sprayed with PP plastic
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Direction of air flow	"A"
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity (F)/environmental protection class (H)	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None, open rotor
Cooling bore / aperture	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Tach output - Output limit - Motor current limit - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Over-temperature protected electronics / motor - Line undervoltage detection
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	PTC resistor
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1; CE
Approval	CSA C22.2 No.77; UL 1004-7 + 60730

EC axial fan

sickled blades (S series)
with guard grille for full nozzle

Product drawing



- | | |
|---|---|
| 1 | Direction of air flow "A" |
| 2 | Connection line PVC AWG20, 3x lead tips crimped |
| 3 | Connection line PVC AWG22, 4x lead tips crimped |




EC axial fan

sickled blades (S series)

with guard grille for full nozzle

Connection screen




No.	Conn.	Designation	Colour	Function / assignment
	CON10	L	black	Mains connection, power supply, phase, see type plate for voltage range
	CON11	N	blue	Mains connection, power supply, neutral conductor, see type plate for voltage range
	CON12	PE	green/yellow	Earth connection
	2	0- 10V PWM	yellow	0-10 V/PWM control input, R _i =100 kΩ, SELV
	4	Tach	white	Speed monitoring output, open collector, 1 pulse per revolution, I _{sink} max = 10 mA, SELV
	3	+10 V	red	Fixed voltage output 10 VDC +/-3 %, I _{max} . 10 mA, short-circuit-proof, power supply for ext. devices (e.g. potentiometer), SELV
	1	GND	blue	Signal ground for control interface, SELV

EC axial fan

sickled blades (S series)

with guard grille for full nozzle

Charts: Air flow 50 Hz



Measurement: LU-161584-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	inH2O
1	230	50	1690	113	0.95	60	67	2765	0	1625	0.00
2	230	50	1675	121	1.01	59	66	2460	40	1450	0.16
3	230	50	1660	128	1.07	59	66	2020	80	1190	0.32
4	230	50	1635	140	1.10	59	67	1495	120	880	0.48
5	230	50	1500	79	0.66	57	64	2450	0	1445	0.00
6	230	50	1500	87	0.73	56	63	2205	32	1300	0.13
7	230	50	1500	95	0.79	57	63	1825	66	1075	0.26
8	230	50	1500	102	0.85	57	64	1365	100	805	0.40
9	230	50	1300	51	0.43	54	60	2125	0	1250	0.00
10	230	50	1300	57	0.47	53	59	1915	24	1125	0.10
11	230	50	1300	62	0.52	53	60	1585	49	930	0.20
12	230	50	1300	67	0.55	53	61	1185	75	695	0.30
13	230	50	1100	31	0.26	49	56	1800	0	1060	0.00
14	230	50	1100	34	0.29	48	55	1620	17	955	0.07
15	230	50	1100	38	0.31	49	56	1340	35	790	0.14
16	230	50	1100	40	0.34	49	56	1000	54	590	0.22

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · q_v = Air flow
p_{fs} = Pressure increase

