

EC axial fan

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

S3G350-AC58-11 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	S3G350-AC58-11	
Motor	M3G074-CF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1450
Power consumption	W	134
Current draw	A	1
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Technical description


Weight	3.9 kg
Size	350 mm
Motor size	74
Rotor surface	Cast in PA plastic
Blade material	PA plastic
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	V
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1; F3-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Power limiter - Motor current limitation - Soft start - Thermal overload protection for motor
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) internally connected
Approval	CCC



EC axial fan

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Product drawing




1	Airflow direction "V"
2	Cable PVC AWG18, 3x crimped ferrules



EC axial fan

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Connection diagram




1	PE, green/yellow	2	N, blue	3	L, black
---	------------------	---	---------	---	----------



EC axial fan

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-116952-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _V	p _{fs}	q _V	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	230	50	1450	72	0.55	2885	0	1700	0.00
2	230	50	1455	96	0.72	2500	40	1470	0.16
3	230	50	1455	111	0.83	2135	70	1255	0.28
4	230	50	1450	134	1.00	1645	102	965	0.41
5	230	50	1250	46	0.35	2485	0	1460	0.00
6	230	50	1250	61	0.46	2150	30	1265	0.12
7	230	50	1250	71	0.53	1835	52	1080	0.21
8	230	50	1250	84	0.61	1415	74	830	0.30
9	230	50	1000	23	0.18	1985	0	1170	0.00
10	230	50	1000	31	0.23	1720	19	1010	0.08
11	230	50	1000	36	0.27	1470	33	865	0.13
12	230	50	1000	43	0.31	1130	48	665	0.19
13	230	50	750	10.0	0.08	1490	0	875	0.00
14	230	50	750	13	0.10	1290	11	760	0.04
15	230	50	750	15	0.11	1100	19	650	0.08
16	230	50	750	18	0.13	850	27	500	0.11

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_V = Air flow · p_{fs} = Pressure increase

