

with guard grille

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	S3G500-ZQ12-90	
Motor	M3G112-IA	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1870
Power consumption	W	1950
Current draw	A	3.0
Max. back pressure	Pa	500
Max. back pressure	in. wg	2.01
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	49.4	35.3	09 Power consumption P_{ed}	kW	1.83
02 Measurement category	A			09 Air flow q_v	m³/h	8645
03 Efficiency category	Static			09 Pressure increase p_{fs}	Pa	372
04 Efficiency grade N	54.1		40	10 Speed (rpm) n	min ⁻¹	1875
05 Variable speed drive	Yes			11 Specific ratio*		1.00

Data obtained at optimum efficiency level.

* Specific ratio = $1 + p_s / 100\,000\text{ Pa}$

LU-204672

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

Technical description


Weight	19.2 kg
Size	500 mm
Motor size	112
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum, painted gray
Impeller material	PP plastic, galvanized sheet-metal plate
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Electronic motor protection

EC axial panel fan - AxiEco

with guard grille


Protection class assignment	I; If a protective earth is connected by the customer This component for installation may have several local protection classes. This information relates to this component's basic design. The final protection class is based on the component's intended installation and connection.
Conformity with standards	EN 61800-5-1; CE
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730-1

Product drawing



1	Airflow direction "V"
2	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm (The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
3	Tightening torque 1.5 ± 0.2 Nm
4	Accessory part: Inlet ring 50100-2-4013 not included in scope of delivery


Accessory part



Inlet ring 50100-2-4013

with guard grille

Connection diagram




No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V / PWM, R _i =100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Fan modulation level Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, P _{max} =800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

Terminal/plug assignment

○ configurable option			configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification	configurable IO mode	CON2																																
IO1	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D158 [0]	source: set value	○	switch: fan enable / disable	D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]																				
	○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D158 [2]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	INPUT	D147 [...]	source: sensor value	D104 [...]	switch: parameter set: #1 / #2	D12E [...]	switch: tach out	signal: tach out	signal: diagnostics out	D130 [0]	D130 [1]	D130 [2]	D130 [5]	D130 [1]	D130 [4]														
	○ Tach out (open collector output)	U _{max} = 50VDC, I _{max} = 20mA, SELV	D158 [5]	○	switch: parameter set: #1 / #2	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]																													
	○ Diagnostics out (open collector output)	U _{max} = 50VDC, I _{max} = 20mA, SELV	D158 [6]	○	switch: parameter set: #1 / #2	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]																switch: fan enable / disable	D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]
IO2	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [0]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	INPUT	D147 [...]	source: sensor value	D104 [...]	switch: parameter set: #1 / #2	D12E [...]	switch: tach out	signal: tach out	signal: diagnostics out	D130 [0]	D130 [1]	D130 [2]	D130 [5]	D130 [1]	D130 [4]														
	○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [2]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]																													
	○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV	D159 [3]	○	switch: parameter set: #1 / #2	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]																switch: fan enable / disable	D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]
	IO3	○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [0]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	INPUT	D147 [...]	source: sensor value	D104 [...]	switch: parameter set: #1 / #2	D12E [...]	switch: tach out	signal: tach out	signal: diagnostics out	D130 [0]	D130 [1]	D130 [2]	D130 [5]	D130 [1]	D130 [4]													
○ Din3 (active low): digital input		active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC	D15A [1]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	switch: fan enable / disable																D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]
○ PWMIn3: digital input, idle level high		PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [7]	○	switch: parameter set: #1 / #2	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	switch: fan enable / disable																D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]
IO3		○ PWMIn3: digital input, idle level low	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [8]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	INPUT	D147 [...]	source: sensor value	D104 [...]	switch: parameter set: #1 / #2	D12E [...]	switch: tach out	signal: tach out	signal: diagnostics out	D130 [0]	D130 [1]	D130 [2]	D130 [5]	D130 [1]	D130 [4]													
	○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [4]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	switch: fan enable / disable																D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]
	○ Tacho out (pulses), analog output	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [5]	○	switch: parameter set: #1 / #2	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	switch: fan enable / disable																D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]
	○ Diagnostics out (pulses)	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	○	switch: parameter set: #1 / #2	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	switch: fan enable / disable	D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]															
RSA RSB	RS485 bus connection,	MODBUS RTU, specification V6.3, SELV		○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]	INPUT	D147 [...]	source: sensor value	D104 [...]	switch: parameter set: #1 / #2	D12E [...]	switch: tach out	signal: tach out	signal: diagnostics out	D130 [0]	D130 [1]	D130 [2]	D130 [5]	D130 [1]	D130 [4]														
Vout	voltage output	voltage parameterizable 3.3..24VDC +/- 5%, P _{max} =800mW, short-circuit-proof, supply for external devices, SELV	D16E [...]	○	switch: control function: heating (pos.) / cooling (neg.)	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]																switch: fan enable / disable	D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]
	alternatively: input auxiliary power supply for parameterization via RS485/Modbus RTU without line voltage	15..50VDC		○	switch: parameter set: #1 / #2	○	switch: direction of rotation: cw / ccw	D148 [...]	switch: set value source	D16C [...]																switch: fan enable / disable	D16A [...]	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [1]	pulse output for auto-addressing	D130 [4]

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-219626-1
Date: 2022-02-24
Nozzle: 50100-2-4013

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _V	p _{fs}	q _V	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	3~	400	50	1870	1350	2.20	77	84	88	12620	0	7430	0.00
2	3~	400	50	1870	1588	2.54	73	80	85	10810	180	6360	0.72
3	3~	400	50	1870	1774	2.81	73	80	85	8205	350	4830	1.41
4	3~	400	50	1865	1950	3.00	81	87	92	4755	500	2800	2.01
5	3~	400	50	1600	839	1.37	73	80	84	10770	0	6340	0.00
6	3~	400	50	1600	1001	1.60	70	77	81	9265	132	5455	0.53
7	3~	400	50	1600	1118	1.77	69	76	81	7035	259	4140	1.04
8	3~	400	50	1600	1195	1.88	77	84	88	4075	369	2400	1.48
9	3~	400	50	1300	450	0.73	68	75	79	8750	0	5150	0.00
10	3~	400	50	1300	537	0.86	64	71	76	7530	87	4430	0.35
11	3~	400	50	1300	600	0.95	64	71	76	5715	171	3365	0.69
12	3~	400	50	1300	641	1.01	72	78	83	3310	243	1950	0.98
13	3~	400	50	1000	205	0.33	61	68	72	6730	0	3960	0.00
14	3~	400	50	1000	244	0.39	58	65	69	5790	51	3410	0.20
15	3~	400	50	1000	273	0.43	57	64	70	4400	101	2590	0.41
16	3~	400	50	1000	292	0.46	65	72	76	2545	144	1500	0.58

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_V = Air flow · p_{fs} = Pressure increase