

EC axial fan - HyBlade

sickled blades (S series)
with guard grille for full nozzle

S3G650-CM04-H6 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	S3G650-CM04-H6	
Motor	M3G084-GF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Type of data definition		ml
Speed (rpm)	min ⁻¹	900
Power input	W	450
Current draw	A	2.0
Max. back pressure	Pa	90
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

		Actual	Request 2015
01 Overall efficiency η_{es}	%	43.4	31.4
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		52	40
05 Variable speed drive		Yes	

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

09 Power input P_{ed}	kW	0.44
09 Air flow q_v	m³/h	6965
09 Pressure increase p_{fs}	Pa	90
10 Speed (rpm) n	min ⁻¹	900
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-162814



Technical features


Mass	9.5 kg
Size	650 mm
Surface of rotor	Coated in black
Material of terminal box	PP plastic
Material of electronics housing	Die-cast aluminium, coated in black
Material of blades	Press-fitted sheet steel blank, sprayed with PP plastic
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Direction of air flow	"A"
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 55
Insulation class	"F"
Humidity (F)/environmental protection class (H)	F4-1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display - Alarm relay - Integrated PID controller - Output limit - Motor current limit - PFC, active - RS485 MODBUS RTU - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1; EN 60335-1; CE
Approval	C22.2 Nr.77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730

EC axial fan - HyBlade

sickled blades (S series)

with guard grille for full nozzle

Product drawing




1	Direction of air flow "A"
2	Connection line PVC AWG22, 5x crimped core-end sleeves
3	Connection line PVC AWG18, 5x crimped core-end sleeves

EC axial fan - HyBlade

sickled blades (S series)

with guard grille for full nozzle


Connection screen



No.	Conn.	Designation	Colour	Function / assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	N	blue	Supply voltage, neutral conductor, 50/60 Hz
1	5	L	black	Supply voltage, phase, 50/60 Hz
1	6	NC	white 1	Status relay, floating status contact; break for failure, contact rating 250 VAC / 2A (AC1) min. 10 mA, basic insulation on mains side and reinforced insulation on control interface side
1	7	COM	white 2	Status relay, floating status contact; common connection, contact rating 250 VAC / 2A (AC1) min. 10 mA, basic insulation on mains side and reinforced insulation on control interface side
2	8	0-10V	yellow	Analogue input 1 (set value); 0-10 V; Ri=100kΩ; parametrisable curve
2	10	RSB	brown	RS485 interface for Modbus, RSB
2	11	RSA	white	RS485 interface for Modbus, RSA
2	12	GND	blue	Reference ground for control interface, SELV
2	13	+10V	red	Fixed voltage output 10 VDC; +10 V +/-3%; max. 10 mA; short-circuit-proof; power supply for external devices (e.g. potentiometer)



Charts: Air flow 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-162814-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	inH ₂ O
1	230	50	900	281	1.26	59	66	65	11210	0	6600	0.00
2	230	50	900	343	1.52	60	66	65	10045	30	5910	0.12
3	230	50	900	393	1.73	60	66	65	8675	60	5105	0.24
4	230	50	900	450	2.00	61	68	68	6905	90	4065	0.36
5	230	50	750	162	0.73	55	61	61	9345	0	5500	0.00
6	230	50	750	198	0.88	55	61	60	8365	21	4925	0.08
7	230	50	750	227	1.00	55	61	60	7230	42	4255	0.17
8	230	50	750	259	1.14	56	64	63	5750	63	3385	0.25
9	230	50	600	83	0.37	49	56	55	7475	0	4400	0.00
10	230	50	600	101	0.45	49	55	54	6690	14	3940	0.06
11	230	50	600	116	0.51	49	56	55	5780	27	3405	0.11
12	230	50	600	132	0.58	51	58	58	4600	40	2710	0.16
13	230	50	450	35	0.16	42	48	48	5605	0	3300	0.00
14	230	50	450	43	0.19	42	48	47	5020	8	2955	0.03
15	230	50	450	49	0.22	42	48	47	4335	15	2555	0.06
16	230	50	450	56	0.25	44	51	50	3450	23	2030	0.09

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · LwA_{out} = Sound power level outlet side
q_v = Air flow · p_{fs} = Pressure increase

