

# AC axial fan

straight blades (A series), single inlet  
with guard grille for full nozzle

S4D250-CA36-12 ebmpapst Datasheet

[sales@fansco.com](mailto:sales@fansco.com)

[www.fansco.com](http://www.fansco.com)

## Nominal data

| Type                          | S4D250-CA36-12    |      |      |      |      |
|-------------------------------|-------------------|------|------|------|------|
| Motor                         | M4D068-CF         |      |      |      |      |
| Phase                         |                   | 3~   | 3~   | 3~   | 3~   |
| Nominal voltage               | VAC               | 230  | 230  | 400  | 400  |
| Connection                    |                   | Δ    | Δ    | Y    | Y    |
| Frequency                     | Hz                | 50   | 60   | 50   | 60   |
| Type of data definition       |                   | fa   | fa   | fa   | fa   |
| Valid for approval / standard |                   | CE   | CE   | CE   | CE   |
| Speed (rpm)                   | min <sup>-1</sup> | 1420 | 1640 | 1420 | 1640 |
| Power input                   | W                 | 27   | 33   | 27   | 33   |
| Current draw                  | A                 | 0.14 | 0.12 | 0.08 | 0.07 |
| Max. back pressure            | Pa                | 100  | 110  | 100  | 110  |
| Min. ambient temperature      | °C                | -25  | -25  | -25  | -25  |
| Max. ambient temperature      | °C                | 85   | 85   | 85   | 85   |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit  
Subject to alterations



# AC axial fan

straight blades (A series), single inlet  
with guard grille for full nozzle

## Technical features


|                                                                    |                                                                 |
|--------------------------------------------------------------------|-----------------------------------------------------------------|
| Mass                                                               | 1.7 kg                                                          |
| Size                                                               | 250 mm                                                          |
| Surface of rotor                                                   | Coated in black                                                 |
| Material of blades                                                 | Sheet steel, coated in black                                    |
| Material of guard grille                                           | Steel, coated in black plastic (RAL9005)                        |
| Direction of air flow                                              | "V"                                                             |
| Direction of rotation                                              | Counter-clockwise, seen on rotor                                |
| Type of protection                                                 | IP 44; Depending on installation and position as per EN 60034-5 |
| Insulation class                                                   | "B"                                                             |
| Humidity (F)/environmental protection class (H)                    | H0+                                                             |
| Max. permissible ambient motor temp. (transp./ storage)            | + 80 °C                                                         |
| Min. permissible ambient motor temp. (transp./storage)             | - 40 °C                                                         |
| Mounting position                                                  | Shaft horizontal or rotor on bottom; rotor on top on request    |
| Condensate discharge holes                                         | Rotor-side                                                      |
| Operation mode                                                     | S1                                                              |
| Motor bearing                                                      | Ball bearing                                                    |
| Touch current acc. IEC 60990 (measuring network Fig. 4, TN system) | < 0.75 mA                                                       |
| Motor protection                                                   | Thermal overload protector (TOP) brought out, basic insulation  |
| Cable exit                                                         | Lateral                                                         |
| Protection class                                                   | I (if protective earth is connected by customer)                |
| Product conforming to standard                                     | EN 60335-1; CE                                                  |



# AC axial fan

straight blades (A series), single inlet  
with guard grille for full nozzle

## Product drawing




- |   |                                             |
|---|---------------------------------------------|
| 1 | Direction of air flow "V"                   |
| 2 | Connection line AWG20, 9x lead tips crimped |



# AC axial fan

straight blades (A series), single inlet  
with guard grille for full nozzle

Connection screen




Note: Change in direction of rotation by reversing two phases

|    |                  |    |                 |     |        |
|----|------------------|----|-----------------|-----|--------|
| Δ  | Delta connection | Y  | Star connection | L1  | black  |
| L2 | blue             | L3 | brown           | U1  | black  |
| V1 | blue             | W1 | brown           | U2  | green  |
| V2 | white            | W2 | yellow          | TOP | 2xgrey |
| PE | green/yellow     |    |                 |     |        |



AC axial fan  
straight blades (A series), single inlet  
with guard grille for full nozzle

Charts: Air flow 50 Hz



Measurement: LU-55427-1

Air performance measured as per ISO 5801  
Installation category A. For detailed  
information on the measuring set-up, please  
contact ebm-papst. Suction-side noise  
levels: L<sub>wA</sub> measured as per ISO 13347 /  
L<sub>pA</sub> measured with 1m distance to fan axis.  
The values given are valid under the  
measuring conditions mentioned above and  
may vary according to the actual installation  
situation. With any deviation from the  
standard set-up, the specific values have to  
be checked and reviewed with the unit  
installed.

Measured values


|   | U   | f  | n                 | P <sub>e</sub> | I    | qv   | p <sub>fs</sub> | qv  | p <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|------|-----------------|-----|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h | Pa              | CFM | inH2O           |
| 1 | 400 | 50 | 1420              | 27             | 0.08 | 920  | 0               | 540 | 0.00            |
| 2 | 400 | 50 | 1410              | 28             | 0.08 | 830  | 15              | 485 | 0.06            |
| 3 | 400 | 50 | 1405              | 29             | 0.08 | 745  | 25              | 440 | 0.10            |
| 4 | 400 | 50 | 1405              | 29             | 0.08 | 620  | 35              | 365 | 0.14            |

U = Supply voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power input · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase



AC axial fan  
straight blades (A series), single inlet  
with guard grille for full nozzle

Charts: Air flow 60 Hz



Measurement: LU-55428-1

Air performance measured as per ISO 5801  
Installation category A. For detailed  
information on the measuring set-up, please  
contact ebm-papst. Suction-side noise  
levels: LwA measured as per ISO 13347 /  
LpA measured with 1m distance to fan axis.  
The values given are valid under the  
measuring conditions mentioned above and  
may vary according to the actual installation  
situation. With any deviation from the  
standard set-up, the specific values have to  
be checked and reviewed with the unit  
installed.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|-------------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | CFM            | inH <sub>2</sub> O |
| 1 | 400 | 60 | 1640              | 33             | 0.07 | 1060              | 0               | 625            | 0.00               |
| 2 | 400 | 60 | 1625              | 35             | 0.08 | 985               | 15              | 580            | 0.06               |
| 3 | 400 | 60 | 1615              | 36             | 0.08 | 885               | 30              | 520            | 0.12               |
| 4 | 400 | 60 | 1610              | 37             | 0.08 | 710               | 45              | 420            | 0.18               |

U = Supply voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power input · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

