

AC axial fan

sickled blades (S series)
with guard grille for short nozzle

S4D400-AS04-85 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	S4D400-AS04-85				
Motor	M4D074-GA				
Phase		3~	3~	3~	3~
Nominal voltage	VAC	400	400	400	400
Connection		Δ	Y	Δ	Y
Frequency	Hz	50	50	60	60
Type of data definition		fa	fa	fa	fa
Valid for approval / standard		CE	CE	CE	CE
Speed (rpm)	min ⁻¹	1370	1070	1490	970
Power input	W	225	160	330	175
Current draw	A	0.46	0.28	0.58	0.33
Max. back pressure	Pa	120	55	80	30
Min. ambient temperature	°C	-40	-40	-40	-40
Max. ambient temperature	°C	50	50	35	35

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

		Actual	Request 2015			
01 Overall efficiency η_{es}	%	30	30	09 Power input P_e	kW	0.26
02 Measurement category		A		09 Air flow q_v	m³/h	3540
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	80
04 Efficiency grade N		40	40	10 Speed (rpm) n	min ⁻¹	1335
05 Variable speed drive		No		11 Specific ratio*		1.00

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-42301



AC axial fan

sickled blades (S series)
with guard grille for short nozzle

Technical features

Mass	6.9 kg
Size	400 mm
Surface of rotor	Coated in black
Material of terminal box	ABS plastic
Material of blades	Sheet steel, coated in black
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 44; Depending on installation and position as per EN 60034-5
Insulation class	"B"
Humidity (F)/environmental protection class (H)	F2-2
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	< 0.75 mA
Electrical leads	Via terminal box
Motor protection	Thermal overload protector (TOP) brought out, basic insulation
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1; CE
Approval	EAC




AC axial fan

sickled blades (S series)

with guard grille for short nozzle

Product drawing




1	Direction of air flow "V"
2	Tightening torque 0.5 ± 0.1 Nm
3	Cable diameter: max. 7.5 mm, tightening torque 1.3 ± 0.2 Nm

AC axial fan

sickled blades (S series)
with guard grille for short nozzle

Connection screen




Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2 x grey
PE	green / yellow				



AC axial fan

sickled blades (S series)
with guard grille for short nozzle

Charts: Air flow 50 Hz Δ



Measurement: LU-42301-1
Measurement: LU-42303-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{WA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	Conn.	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	Δ	400	50	1370	225	0.46	4930	0	2900	0.00
2	Δ	400	50	1350	245	0.49	4315	40	2540	0.16
3	Δ	400	50	1340	262	0.52	3770	70	2220	0.28
4	Δ	400	50	1320	283	0.55	2965	100	1745	0.40
5	Y	400	50	1070	160	0.28	3855	0	2270	0.00
6	Y	400	50	1020	165	0.29	3260	23	1920	0.09
7	Y	400	50	980	170	0.30	2750	37	1620	0.15
8	Y	400	50	940	176	0.31	2105	51	1240	0.20


Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase



AC axial fan

sickled blades (S series)
with guard grille for short nozzle

Charts: Air flow 60 Hz Δ



Measurement: LU-42302-1
Measurement: LU-42304-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	Conn.	U	f	n	P _e	I	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	Δ	400	60	1490	330	0.58	5375	0	3165	0.00
2	Δ	400	60	1470	346	0.62	4970	25	2925	0.10
3	Δ	400	60	1440	361	0.65	4550	50	2675	0.20
4	Δ	400	60	1405	381	0.68	3910	80	2300	0.32
5	Y	400	60	970	175	0.33	3515	0	2070	0.00
6	Y	400	60	945	177	0.33	3190	10	1875	0.04
7	Y	400	60	910	179	0.33	2875	20	1695	0.08
8	Y	400	60	875	180	0.34	2430	31	1430	0.12

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · q_v = Air flow · P_{fs} = Pressure increase

