

AC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

S4D420-AU06-43 ebmpapst Datasheet FansCo

sales@fansco.com

www.fansco.com

Nominal data

Type	S4D420-AU06-43				
Motor	M4D094-EA				
Phase		3~	3~	3~	3~
Nominal voltage	VAC	230	230	400	400
Wiring		Δ	Δ	Y	Y
Frequency	Hz	50	60	50	60
Method of obtaining data		ml	ml	ml	ml
Valid for approval/standard		CE	CE	CE	CE
Speed (rpm)	min ⁻¹	1360	1490	1360	1490
Power consumption	W	250	380	250	380
Current draw	A	0.85	1.11	0.49	0.64
Max. back pressure	Pa	80	110	80	110
Max. back pressure	inH ₂ O	0.32	0.44	0.32	0.44
Min. ambient temperature	°C	-25	-25	-25	-25
Max. ambient temperature	°C	65	60	65	60
Starting current	A	2.95	2.8	1.7	1.62

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	32.7	30	09 Power consumption P_e	kW	0.26
02 Measurement category		A		09 Air flow q_v	m ³ /h	3210
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	96
04 Efficiency grade N		42.7	40	10 Speed (rpm) n	min ⁻¹	1355
05 Variable speed drive		No		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-71120



AC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Technical description

Weight	7 kg
Fan size	420 mm
Rotor surface	Painted black
Terminal box material	ABS plastic, black
Blade material	Press-fitted sheet steel blank, sprayed with PP plastic
Guard grille material	Steel, coated with black plastic (RAL 9005)
Airflow direction	"V"
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F4-1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Via terminal box
Motor protection	Thermal overload protector (TOP) with basic insulation
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60034-1 (2010); CE




S4D420-AU06-43

AC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Product drawing




1	Direction of air flow "V"
2	Tightening torque 0.8 ± 0.15 Nm
3	Cable diameter min. 6 mm, max. 12 mm; tightening torque $2 \text{ Nm} \pm 0.2$ Nm



AC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Connection diagram




Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2x gray
PE	green/yellow				



AC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Curves: Air performance 50 Hz Y



Measurement: LU-71120-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	CFM	inH2O
1	Y	400	50	1395	202	0.45	5015	0	2950	0.00
2	Y	400	50	1385	220	0.47	4615	30	2715	0.12
3	Y	400	50	1375	232	0.48	4210	55	2475	0.22
4	Y	400	50	1360	250	0.49	3705	80	2180	0.32


Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase



AC axial fan

sickle-shaped blades (S series)
with guard grille for short nozzle

Curves: Air performance 60 Hz Y



Measurement: LU-120308-1
Measurement: LU-71121-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	CFM	inH2O
1	Y	460	60	1615	303	0.49	5890	0	3465	0.00
2	Y	460	60	1590	336	0.53	5370	44	3160	0.18
3	Y	460	60	1570	365	0.56	4680	88	2755	0.35
4	Y	460	60	1540	400	0.60	3960	120	2330	0.48
5	Y	400	60	1570	306	0.52	5640	0	3320	0.00
6	Y	400	60	1540	332	0.56	5115	40	3010	0.16
7	Y	400	60	1520	353	0.59	4465	80	2630	0.32
8	Y	400	60	1490	380	0.64	3770	110	2220	0.44

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

