

# AC axial fan

straight blades (A series)

with guard grille for short nozzle

**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

|                             |                   |      |      |
|-----------------------------|-------------------|------|------|
| Type                        | S4E315-DC44-09    |      |      |
| Motor                       | M4E068-DF         |      |      |
| Phase                       |                   | 1~   | 1~   |
| Nominal voltage             | VAC               | 230  | 230  |
| Frequency                   | Hz                | 50   | 60   |
| Method of obtaining data    |                   | ce   | ce   |
| Valid for approval/standard |                   | CE   | CE   |
| Speed (rpm)                 | min <sup>-1</sup> | 1340 | 1420 |
| Power consumption           | W                 | 110  | 140  |
| Current draw                | A                 | 0.50 | 0.62 |
| Capacitor                   | µF                | 3    | 3    |
| Capacitor voltage           | VDB               | 400  | 400  |
| Min. ambient temperature    | °C                | -40  | -40  |
| Max. ambient temperature    | °C                | -    | 55   |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change



# AC axial fan

straight blades (A series)

with guard grille for short nozzle

## Technical description

|                                                                            |                                                              |
|----------------------------------------------------------------------------|--------------------------------------------------------------|
| Weight                                                                     | 3.2 kg                                                       |
| Fan size                                                                   | 315 mm                                                       |
| Rotor surface                                                              | Painted black                                                |
| Impeller material                                                          | Sheet steel, hot-dip galvanized                              |
| Guard grille material                                                      | Steel, phosphated and coated with black plastic              |
| Number of blades                                                           | 5                                                            |
| Airflow direction                                                          | "V"                                                          |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                        |
| Degree of protection                                                       | IP44; installation- and position-dependent as per EN 60034-5 |
| Insulation class                                                           | "F"                                                          |
| Moisture (F) / Environmental (H) protection class                          | F2-2                                                         |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                      |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                      |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request |
| Condensation drainage holes                                                | On rotor side                                                |
| Mode                                                                       | S1                                                           |
| Motor bearing                                                              | Ball bearing with low-temperature lubricant                  |
| Speed levels                                                               | 2                                                            |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                    |
| Electrical hookup                                                          | Via terminal box, capacitor integrated and connected         |
| Motor protection                                                           | Thermal overload protector (TOP) internally connected        |
| With cable                                                                 | Axial                                                        |
| Protection class                                                           | I (with customer connection of protective earth)             |
| Motor capacitor according to EN 60252-1 in safety protection class         | S0                                                           |
| Conformity with standards                                                  | EN 60335-1; CE                                               |
| Approval                                                                   | CCC; EAC                                                     |




# AC axial fan

straight blades (A series)

with guard grille for short nozzle

## Product drawing




|   |                                                                         |
|---|-------------------------------------------------------------------------|
| 1 | Direction of air flow "V"                                               |
| 2 | Tightening torque $0.7 \pm 0.2$ Nm                                      |
| 3 | Shown without terminal box cover                                        |
| 4 | Cable diameter min. 4 mm, max. 8 mm; tightening torque $1.3 \pm 0.2$ Nm |

# AC axial fan

straight blades (A series)  
with guard grille for short nozzle

Connection diagram



Note: High speed (step II); low speed (step I)


|   |              |   |               |   |        |
|---|--------------|---|---------------|---|--------|
| 1 | = N = blue   | 2 | brown         | 3 | yellow |
| 4 | Step I white | 5 | Step II black | 6 | PE     |



# AC axial fan

straight blades (A series)  
with guard grille for short nozzle

## Curves: Air performance 50 Hz



Measurement: LU-30261-1  
Measurement: LU-30262-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values


|   | Stage | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | q <sub>v</sub> | p <sub>fs</sub>    |
|---|-------|-----|----|-------------------|----------------|------|-------------------|----------------|--------------------|
|   |       | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | cfm            | inH <sub>2</sub> O |
| 1 | 2     | 230 | 50 | 1340              | 110            | 0.50 | 1425              | 840            | 0.00               |
| 2 | 1     | 230 | 50 | 1125              | 99             | 0.43 | 1195              | 705            | 0.00               |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow



AC axial fan  
straight blades (A series)  
with guard grille for short nozzle

Curves: Air performance 60 Hz



Measurement: LU-50073-1  
Measurement: LU-50074-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | Stage | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | q <sub>v</sub> | p <sub>fs</sub>    |
|---|-------|-----|----|-------------------|----------------|------|-------------------|----------------|--------------------|
|   |       | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | cfm            | inH <sub>2</sub> O |
| 1 | 2     | 230 | 60 | 1420              | 140            | 0.62 | 1600              | 945            | 0.00               |
| 2 | 1     | 230 | 60 | 1010              | 103            | 0.45 | 1120              | 660            | 0.00               |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow

