

AC axial fan - HyBlade

sickled blades (S series)

S8D910-CE01-01 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	S8D910-CE01-01				
Motor	M8D138-LA				
Phase		3~	3~	3~	3~
Nominal voltage	VAC	400	400	480	480
Connection		Δ	Y	Δ	Y
Frequency	Hz	50	50	60	60
Type of data definition		ml	ml	ml	ml
Valid for approval / standard		CE	CE	CE	CE
Speed (rpm)	min ⁻¹	670	515	775	545
Power input	W	910	560	1450	800
Current draw	A	2.27	1.16	2.7	1.45
Max. back pressure	Pa	90	54	125	62
Min. ambient temperature	°C	-40	-40	-40	-40
Max. ambient temperature	°C	80	80	55	55
Starting current	A	6.1	2.0	6.54	2.2

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

		Actual	Request 2015			
01 Overall efficiency η_{es}	%	34.8	33.3	09 Power input P_e	kW	0.88
02 Measurement category		A		09 Air flow q_v	m³/h	13940
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	80
04 Efficiency grade N		41.5	40	10 Speed (rpm) n	min ⁻¹	670
05 Variable speed drive		No		11 Specific ratio*		1.00

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.


* Specific ratio = $1 + p_g / 100\,000\text{ Pa}$ LU-160563



Technical features

Mass	33.3 kg
Size	910 mm
Surface of rotor	Cast in aluminium
Material of terminal box	PP plastic
Material of blades	Aluminium sheet insert, sprayed with PP plastic
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Blade angle	-5°
Direction of air flow	"V"
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity (F)/environmental protection class (H)	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	On rotor and stator sides
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Thermal overload protector (TOP) brought out, basic insulation
Cable exit	Axial
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60034-1 (2010); EN 61800-5-1; CE
Approval	VDE; EAC

Product drawing




1	Direction of air flow "V"
2	Tightening torque 1.5 Nm±0.2 Nm
3	Cable diameter: min. 7 mm, max. 14 mm, tightening torque 2±0.3 Nm

AC axial fan - HyBlade

sickled blades (S series)


Connection screen



Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2 x grey
PE	green/yellow				



Charts: Air flow 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-160563-1
Measurement: LU-161729-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.


Measured values

	Conn.	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa	cfm	inH ₂ O
1	Δ	400	50	705	617	2.06	64	71	71	21290	0	12530	0.00
2	Δ	400	50	690	730	2.16	62	69	69	18895	30	11120	0.12
3	Δ	400	50	680	825	2.25	60	68	67	16060	60	9455	0.24
4	Δ	400	50	670	910	2.27	64	71	72	12520	90	7370	0.36
5	Y	400	50	600	428	0.93	60	67	66	18480	0	10875	0.00
6	Y	400	50	560	481	1.04	57	64	63	15755	21	9270	0.08
7	Y	400	50	525	519	1.12	54	61	61	12880	39	7580	0.16
8	Y	400	50	515	560	1.16	56	63	63	9705	54	5710	0.22

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase



Charts: Air flow 60 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-160671-1
Measurement: LU-161733-1

Air performance measured as per ISO 5801
Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L_{wA} measured as per ISO 13347 / L_{pA} measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	Conn.	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa	cfm	inH ₂ O
1	Δ	480	60	825	978	2.24	67	75	75	24980	0	14705	0.00
2	Δ	480	60	805	1183	2.48	65	72	72	21470	50	12635	0.20
3	Δ	480	60	785	1334	2.66	64	72	71	17870	90	10515	0.36
4	Δ	480	60	775	1450	2.70	70	77	78	13685	125	8055	0.50
5	Y	480	60	660	639	1.16	62	69	69	20515	0	12075	0.00
6	Y	480	60	590	704	1.29	57	64	64	16365	30	9630	0.12
7	Y	480	60	550	734	1.35	55	63	62	13005	48	7655	0.19
8	Y	480	60	545	800	1.45	58	65	66	9675	63	5695	0.25

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase

