

AC axial fan - HyBlade

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

S8E630-AN01-01 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Muldingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Muldingen GmbH · Headquarters Muldingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

| Type | S8E630-AN01-01 | | |
|-----------------------------|--------------------|------|------|
| Motor | M8E110-GF | | |
| Phase | | 1~ | 1~ |
| Nominal voltage | VAC | 230 | 230 |
| Frequency | Hz | 50 | 60 |
| Method of obtaining data | | ml | ml |
| Valid for approval/standard | | - | - |
| Speed (rpm) | min ⁻¹ | 670 | 710 |
| Power consumption | W | 340 | 460 |
| Current draw | A | 1.72 | 2.12 |
| Capacitor | µF | 7 | 7 |
| Capacitor voltage | VDB | 450 | 450 |
| Max. back pressure | Pa | 60 | 75 |
| Max. back pressure | inH ₂ O | 0.24 | 0.3 |
| Min. ambient temperature | °C | -40 | -40 |
| Max. ambient temperature | °C | 65 | 55 |
| Starting current | A | 5.6 | 4.7 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC axial fan - HyBlade

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Technical description


| | |
|--|--|
| Weight | 17 kg |
| Fan size | 630 mm |
| Rotor surface | Painted black |
| Terminal box material | ABS plastic, black |
| Blade material | Press-fitted sheet steel blank, sprayed with PP plastic |
| Guard grille material | Steel, phosphated and coated with black plastic |
| Number of blades | 5 |
| Blade pitch | -5° |
| Airflow direction | "V" |
| Direction of rotation | Counterclockwise, viewed toward rotor |
| Degree of protection | IP54 |
| Insulation class | "F" |
| Moisture (F) / Environmental (H) protection class | F4-1 |
| Max. permitted ambient temp. for motor (transport/storage) | + 80 °C |
| Min. permitted ambient temp. for motor (transport/storage) | - 40 °C |
| Installation position | Shaft horizontal or rotor on bottom; rotor on top on request |
| Condensation drainage holes | On rotor side |
| Mode | S1 |
| Motor bearing | Ball bearing |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA |
| Electrical hookup | Via terminal box, capacitor integrated and connected |
| Motor protection | Thermal overload protector (TOP) with basic insulation |
| With cable | Axial |
| Protection class | I (with customer connection of protective earth) |
| Motor capacitor according to EN 60252-1 in safety protection class | S0 |
| Conformity with standards | EN 61800-5-1 |
| Approval | UL 1004-1; VDE; EAC; CSA C22.2 No. 100 |



AC axial fan - HyBlade

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Product drawing



| | |
|---|---|
| 1 | Direction of air flow "V" |
| 2 | Tightening torque 0.8±0.15 Nm |
| 3 | Shown without terminal box cover |
| 4 | Cable diameter: min. 6 mm, max. 12 mm; tightening torque 2±0.3 Nm |



AC axial fan - HyBlade

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Connection diagram




| | | | | | |
|----|--------------|-----|-------|---|--------------|
| L | = U1 = blue | Z | brown | N | = U2 = black |
| PE | green/yellow | TOP | gray | | |



AC axial fan - HyBlade

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Curves: Air performance 50 Hz



Measurement: LU-105803-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

| | U | f | n | P _e | I | LpA _{in} | LwA _{in} | LwA _{out} | q _v | p _{fs} | q _v | p _{fs} |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|--------------------|-------------------|-----------------|----------------|--------------------|
| | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | dB(A) | m ³ /h | Pa | cfm | inH ₂ O |
| 1 | 230 | 50 | 700 | 278 | 1.52 | 58 | 64 | 63 | 8450 | 0 | 4975 | 0.00 |
| 2 | 230 | 50 | 690 | 305 | 1.60 | 56 | 62 | 61 | 7310 | 25 | 4305 | 0.10 |
| 3 | 230 | 50 | 680 | 322 | 1.65 | 54 | 61 | 60 | 6335 | 43 | 3730 | 0.17 |
| 4 | 230 | 50 | 670 | 340 | 1.72 | 55 | 62 | 61 | 5275 | 60 | 3105 | 0.24 |


U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase



AC axial fan - HyBlade

sickle-shaped blades (S series), single-intake
with guard grille for short nozzle

Curves: Air performance 60 Hz



Measurement: LU-105807-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

| | U | f | n | P _e | I | LpA _{in} | LwA _{in} | LwA _{out} | q _v | P _{fs} | q _v | P _{fs} |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|--------------------|-------------------|-----------------|----------------|--------------------|
| | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | dB(A) | m ³ /h | Pa | cfm | inH ₂ O |
| 1 | 230 | 60 | 810 | 379 | 1.70 | 61 | 67 | 66 | 9740 | 0 | 5735 | 0.00 |
| 2 | 230 | 60 | 780 | 416 | 1.88 | 57 | 63 | 63 | 8325 | 30 | 4900 | 0.12 |
| 3 | 230 | 60 | 750 | 441 | 2.01 | 56 | 62 | 61 | 6940 | 53 | 4085 | 0.21 |
| 4 | 230 | 60 | 710 | 460 | 2.12 | 58 | 64 | 64 | 5160 | 75 | 3040 | 0.30 |

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · P_{fs} = Pressure increase

