

W1G130-AA25-10 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W1G130-AA25-10	
Motor	M1G055-AI	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50/60
Type of data definition		ml
State		prelim.
Speed	min ⁻¹	2800
Power input	W	16
Current draw	A	0.13
Min. ambient temperature	°C	-30
Max. ambient temperature	°C	70


ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



Technical features


Mass	0.75 kg
Size	130 mm
Material of impeller	PA plastic
Material of wall ring	PP plastic
Number of blades	7
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Soft start - Over-temperature protected motor
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Electrical leads	With plug
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	II
Product conforming to standard	EN 60335-1; CE
Approval	VDE; UL 2111; CSA C22.2 Nr.77

Product drawing




1	Direction of air flow "V"
2	Connection line AWG20, 2x crimped receptacles for tabs 6.3 x 0.8
3	Preferably use 2x Remform screws WN-156-2 5.0x16 Torx galvanised (Arnold). Alternatively use 2x metric M4 screw, mounting provided with nut

Connection screen



Charts: Air flow 50 Hz



Measurement: LU-139739
Measurement: LU-140010

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{wA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	L _{pA_{in}}	L _{wA_{in}}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa
1	230	50	3200	23	0.19	55	63	370	0
2	230	50	3200	24	0.19	53	61	340	30
3	230	50	3200	24	0.19	51	60	300	60
4	230	50	3200	24	0.19	54	63	245	90
5	230	50	2800	16	0.13	51	60	325	0
6	230	50	2800	16	0.13	50	58	300	24
7	230	50	2800	16	0.13	48	57	265	48
8	230	50	2800	16	0.13	51	60	220	71

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · L_{pA_{in}} = Sound pressure level inlet side · L_{wA_{in}} = Sound power level inlet side · qv = Air flow
p_{fs} = Pressure increase

