



W1G130-AA25-16 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Limited partnership · Headquarters Muldingen
 Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Muldingen GmbH · Headquarters Muldingen
 Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

| | | | |
|--------------------------|-------------------|-------|-------|
| Type | W1G130-AA25-16 | | |
| Motor | M1G055-AI | | |
| Phase | | 1~ | 1~ |
| Nominal voltage | VAC | 230 | 230 |
| Frequency | Hz | 50/60 | 50/60 |
| Method of obtaining data | | ml | |
| Speed (rpm) | min ⁻¹ | 2500 | 2200 |
| Power consumption | W | 12 | |
| Current draw | A | 0.1 | |
| Max. back pressure | Pa | 50 | |
| Max. back pressure | in. wg | 0.2 | |
| Min. ambient temperature | °C | -30 | -30 |
| Max. ambient temperature | °C | 60 | 60 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
 Subject to change




Technical description

| | |
|---|---|
| Weight | 0.74 kg |
| Size | 130 mm |
| Motor size | 55 |
| Impeller material | PA plastic |
| Fan housing material | Plastic, PP |
| Number of blades | 7 |
| Airflow direction | V |
| Direction of rotation | Counterclockwise, viewed toward rotor |
| Degree of protection | IP55; only with suitable plug, to be installed by customer |
| Insulation class | "B" |
| Moisture (F) / Environmental (H) protection class | H1+ |
| Max. permitted ambient temp. for motor (transport/storage) | +80 °C |
| Min. permitted ambient temp. for motor (transport/storage) | -40 °C |
| Installation position | Any |
| Condensation drainage holes | None |
| Mode | S1 |
| Motor bearing | Ball bearing |
| Technical features | <ul style="list-style-type: none"> - Speed setting input (230 V) - Soft start - Thermal overload protection for motor |
| Speed levels | 2 |
| EMC immunity to interference | According to EN 61000-6-2 (industrial environment) |
| EMC circuit feedback | According to EN 61000-3-2/3 |
| EMC interference emission | According to EN 61000-6-3 (household environment) |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 0.25 mA |
| Electrical hookup | Plug |
| Motor protection | Thermal switch auto reset, internally connected |
| With cable | Lateral |
| Protection class assignment | <p>II; This component for installation may have several local protection classes. This information relates to this component's basic design.</p> <p>The final protection class is based on the component's intended installation and connection. If there is a PE connection point on the housing, it must not be visible after installation.</p> |
| Safety class of the permissible refrigerants according to EN378 / ISO5149-1 | A3/B3 |
| Maximum surface temperature | 225 °C |
| Conformity with standards | EN 60034-1; EN 60204-1; EN 60335-1; EN 60335-2-24; EN 60335-2-80; EN 60335-2-89; CE; UKCA |
| Comment on CE | Ecodesign Directive 2009/125/EC + Fan Directive (EC) No. 327/2011 does not apply, as power consumption <125W. |
| Approval | UL 1004-3 + 60730-1; CSA C22.2 No. 77 + CAN/CSA-E60730-1; VDE |




Product drawing




| | |
|---|--|
| 1 | Airflow direction "V" |
| 2 | Preferably 2x Remform screws WN-156-2 5.0x16 Torx galvanized from Arnold should be used. Alternatively, 2x metric M4 screws fastened with nuts |
| 3 | Pin S, speed selection (flat plug 2.8 x 0.5) |
| 4 | Pin L1, phase (flat plug 2.8 x 0,5) |
| 5 | Pin N, neutral conductor (flat plug 2.8 x 0.5) |



Connection diagram



Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-186772-1
Measurement: LU-186736-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

| | Stage | U | f | n | P _{ed} | I | LpA _{in} | LwA _{in} | q _v | P _{fs} | q _v | P _{fs} |
|---|-------|-----|----|-------------------|-----------------|------|-------------------|-------------------|-------------------|-----------------|----------------|-----------------|
| | | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | m ³ /h | Pa | cfm | in. wg |
| 1 | 2 | 230 | 50 | 2500 | 11 | 0.10 | 48 | 56 | 280 | 0 | 165 | 0.00 |
| 2 | 2 | 230 | 50 | 2500 | 12 | 0.10 | 47 | 55 | 255 | 20 | 150 | 0.08 |
| 3 | 2 | 230 | 50 | 2500 | 12 | 0.10 | 46 | 55 | 230 | 35 | 135 | 0.14 |
| 4 | 2 | 230 | 50 | 2500 | 12 | 0.10 | 46 | 55 | 195 | 50 | 115 | 0.20 |
| 5 | 1 | 230 | 50 | 2200 | 9.0 | 0.08 | 44 | 53 | 245 | 0 | 145 | 0.00 |
| 6 | 1 | 230 | 50 | 2200 | 9.0 | 0.08 | 43 | 52 | 225 | 16 | 130 | 0.06 |
| 7 | 1 | 230 | 50 | 2200 | 9.0 | 0.08 | 43 | 51 | 200 | 27 | 120 | 0.11 |
| 8 | 1 | 230 | 50 | 2200 | 9.0 | 0.08 | 42 | 51 | 175 | 40 | 100 | 0.16 |

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · P_{fs} = Pressure increase

