

EC axial fan

sickled blades (S series), single inlet
ESM wall ring

W1G172-EC95-11 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W1G172-EC95-11		
Motor	M1G055-BD		
Phase		1~	1~
Nominal voltage	VAC	115	115
Frequency	Hz	50/60	50/60
Type of data definition		ml	
Speed (rpm)	min ⁻¹	2400	900
Power input	W	21	-
Current draw	A	0.3	
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	50	-50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



EC axial fan

sickled blades (S series), single inlet

ESM wall ring

Technical features


Mass	0.9 kg
Size	172 mm
Material of blades	PA plastic
Material of wall ring	PP plastic
Number of blades	5
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity (F)/environmental protection class (H)	H1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Speed selection max/min - Soft start - Over-temperature protected motor
Speed steps	2
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	II
Product conforming to standard	EN 60335-1; CE
Approval	EAC; UL 1004-3; VDE; CSA C22.2 No.77



EC axial fan


sickled blades (S series), single inlet
ESM wall ring

Product drawing



- 1 Direction of air flow "V"
- 2 Connection line 3x AWG20, 3x brass lead tips crimped

Connection screen




EC axial fan

sickled blades (S series), single inlet

ESM wall ring

Charts: Air flow 50 Hz



Measurement: LU-124699-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	115	50	2400	17	0.23	490	0	285	0.00
2	115	50	2400	18	0.25	440	20	260	0.08
3	115	50	2400	21	0.30	390	40	230	0.16
4	115	50	2400	18	0.26	335	55	195	0.22
5	115	50	900	1.00	0.01	185	0	110	0.00
6	115	50	900	1.00	0.01	170	3	100	0.01
7	115	50	900	1.00	0.02	150	6	90	0.02
8	115	50	900	1.00	0.01	125	8	75	0.03

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

