

W1G200-EC44-55

EC axial fan

sickled blades (S series), single inlet
ESM wall ring



W1G200-EC44-55 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W1G200-EC44-55	
Motor	M1G055-BD	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50/60
Type of data definition		ml
Speed (rpm)	min ⁻¹	1400
Power input	W	11
Current draw	A	0.1
Max. back pressure	Pa	24
Min. ambient temperature	°C	-30
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



EC axial fan

sickled blades (S series), single inlet

ESM wall ring

Technical features


Mass	0.9 kg
Size	200 mm
Material of blades	PA plastic
Material of wall ring	PP plastic
Number of blades	5
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54; Only with suitable connector, which has to be fitted by the customer
Insulation class	"B"
Humidity (F)/environmental protection class (H)	H1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output limit - Motor current limit - Soft start - Over-temperature protected electronics / motor
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Motor protection	Locked-rotor protection
Protection class	II
Product conforming to standard	EN 60335-1; CE



EC axial fan


sickled blades (S series), single inlet
ESM wall ring

Product drawing




- | | |
|---|---|
| 1 | Direction of air flow "V" |
| 2 | PIN S, speed selection (flat connector 2.8 x 0.5) |
| 3 | PIN L1, phase (flat connector 2.8 x 0.5) |
| 4 | PIN N, neutral conductor (flat connector 2.8 x 0.5) |

Connection screen



EC axial fan
sickled blades (S series), single inlet
ESM wall ring

Charts: Air flow 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-166603-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	230	50	1400	10.0	0.09	495	0	290	0.00
2	230	50	1400	10.0	0.10	445	10	265	0.04
3	230	50	1400	11	0.10	405	18	240	0.07
4	230	50	1400	11	0.10	370	24	215	0.10

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

