

W1G200-EC91-54

EC axial fan - ESM

sickle-shaped blades (S series), single-intake

ESM fan housing

W1G200-EC91-54 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

| | | |
|--------------------------|-------------------|-------|
| Type | W1G200-EC91-54 | |
| Motor | M1G055-BD | |
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Frequency | Hz | 50/60 |
| Method of obtaining data | | ml |
| Speed | min ⁻¹ | 1500 |
| Power consumption | W | 15 |
| Current draw | A | 0.12 |
| Max. back pressure | Pa | 29 |
| Min. ambient temperature | °C | -30 |
| Max. ambient temperature | °C | 50 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan - ESM

sickle-shaped blades (S series), single-intake

ESM fan housing

Technical description

| | |
|---|--|
| Weight | 0.9 kg |
| Fan size | 200 mm |
| Blade material | PA plastic |
| Fan housing material | PP plastic |
| Number of blades | 5 |
| Airflow direction | "V" |
| Direction of rotation | Counterclockwise, viewed toward rotor |
| Degree of protection | IP54 |
| Insulation class | "B" |
| Moisture (F) / Environmental (H) protection class | H1 |
| Max. permitted ambient temp. for motor (transport/storage) | + 80 °C |
| Min. permitted ambient temp. for motor (transport/storage) | - 40 °C |
| Installation position | Any |
| Condensation drainage holes | None |
| Mode | S1 |
| Motor storage | Ball bearing |
| Technical features | <ul style="list-style-type: none"> - ESM+ expandable with plug-in module - Soft start - Thermal overload protection for motor |
| Motor protection | Thermal overload protector (TOP) internally connected |
| With cable | Lateral |
| Protection class | II |
| Conformity with standards | EN 60335-1; CE |
| Approval | CSA C22.2 No. 77; EAC; UL 1004-3; VDE |




EC axial fan - ESM

sickle-shaped blades (S series), single-intake


ESM fan housing

Product drawing




| | |
|-----|--|
| 1 | Direction of air flow "V" |
| 2 | Cable PVC AWG20, 1x tyco connector 1745082-1 |
| 2.1 | not used |
| 2.2 | N (blue) |
| 2.3 | L (black) |

Connection diagram



Curves: Air performance 50 Hz



$\rho = 1,15 \text{ kg/m}^3 \pm 2\%$

Measurement: LU-113352

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

| | U | f | n | P _{ed} | I | LpA _{in} | LwA _{in} | qv | p _{fs} |
|---|-----|----|-------------------|-----------------|------|-------------------|-------------------|-------------------|-----------------|
| | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | m ³ /h | Pa |
| 1 | 230 | 50 | 1500 | 14 | 0.11 | 46 | 54 | 525 | 0 |
| 2 | 230 | 50 | 1500 | 15 | 0.12 | 46 | 54 | 480 | 10 |
| 3 | 230 | 50 | 1500 | 15 | 0.12 | 46 | 53 | 435 | 20 |
| 4 | 230 | 50 | 1500 | 15 | 0.12 | 47 | 56 | 370 | 29 |

U = Power supply · f = Frequency · n = Speed · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
 qv = Air flow · p_{fs} = Pressure increase

