

W1G200-EC91-57

EC axial fan - ESM

sickled blades (S series), single inlet
ESM wall ring



W1G200-EC91-57 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W1G200-EC91-57	
Motor	M1G055-BD	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50/60
Type of data definition		ml
Speed	min ⁻¹	1250
Power input	W	7
Current draw	A	0.1
Max. back pressure	Pa	20
Min. ambient temperature	°C	-30
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



Technical features


Mass	1 kg
Size	200 mm
Material of blades	PA plastic
Material of wall ring	PP plastic
Number of blades	5
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- ESM+ extensible with plug-in module - Soft start - Over-temperature protected motor
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	II
Product conforming to standard	EN 60335-1; CE
Approval	UL 2111; VDE; CSA C22.2 Nr.77

EC axial fan - ESM

sickled blades (S series), single inlet


ESM wall ring

Product drawing



- | | |
|---|---|
| 1 | Direction of air flow "V" |
| 2 | Connection line AWG20, 2x plug contact Heyco 7033 crimped with connector similar to EMF Corporation P-2-3 |


Connection screen



EC axial fan - ESM

sickled blades (S series), single inlet
ESM wall ring

Charts: Air flow 50 Hz



$\rho = 1,15 \text{ kg/m}^3 \pm 2\%$

Measurement: LU-169694

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{WA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	q _v	P _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa
1	230	50	1250	6.0	0.08	445	0
2	230	50	1250	6.0	0.08	395	8
3	230	50	1250	7.0	0.09	360	14
4	230	50	1250	7.0	0.10	320	20

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

