

EC axial fan - ESM

sickled blades (S series), single inlet
ESM wall ring

W1G200-FA87-14 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W1G200-FA87-14		
Motor	M1G055-BD		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50/60	50/60
Type of data definition		ml	ml
Speed (rpm)	min ⁻¹	900	1300
Power input	W		9
Current draw	A		0.08
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	50	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



EC axial fan - ESM

sickled blades (S series), single inlet

ESM wall ring

Technical features

Mass	1 kg
Size	200 mm
Material of blades	PA plastic
Material of wall ring	PP plastic
Number of blades	5
Direction of air flow	"A"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54; Only with suitable connector, which has to be fitted by the customer
Insulation class	"B"
Humidity (F)/environmental protection class (H)	H1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- ESM+ extensible with plug-in module - Soft start - Over-temperature protected motor
Speed steps	2
Motor protection	Thermal overload protector (TOP) wired internally
Protection class	II
Product conforming to standard	EN 60335-1; EN 60335-2-24; EN 60335-2-80; EN 60335-2-89; CE
Approval	UL 1004-3; CSA C22.2 No.77; VDE




EC axial fan - ESM

sickled blades (S series), single inlet

ESM wall ring

Product drawing




1	Direction of air flow "A"
2	Direction of air flow "V"
3	PIN S, direction of rotation selection (flat connector 2.8x0.5)
4	PIN L1, phase (flat connector 2.8x0.5)
5	PIN N, neutral conductor (flat connector 2.8x0.5)

EC axial fan - ESM

sickled blades (S series), single inlet
ESM wall ring


Connection screen



EC axial fan - ESM

sickled blades (S series), single inlet
ESM wall ring

Charts: Air flow 50 Hz



Measurement: LU-136359-1
Measurement: LU-136364-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{WA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{ts}	q _v	p _{ts}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH ₂ O
1	230	50	1300	8.2	0.07	490	0	290	0.00
2	230	50	1300	7.7	0.07	430	8	250	0.03
3	230	50	1300	8.2	0.07	355	16	210	0.06
4	230	50	1300	9.0	0.08	280	24	165	0.10
5	230	50	900	4.0	0.04	335	0	195	0.00
6	230	50	900	3.9	0.04	295	4	170	0.02
7	230	50	900	3.9	0.04	240	7	140	0.03
8	230	50	900	4.4	0.05	190	11	110	0.04

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · q_v = Air flow · p_{ts} = Pressure increase

