

EC axial fan

sickled blades (S series)
Wall ring with guard grille

W1G250-CB17-01 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W1G250-CB17-01		
Motor	M1G055-BI		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50/60	50/60
Type of data definition			ml
Speed	min ⁻¹	1000	1200
Power input	W	-	16
Current draw	A		0.135
Max. back pressure	Pa		21
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	60	60

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



EC axial fan

sickled blades (S series)

Wall ring with guard grille

Technical features


Mass	1.6 kg
Size	250 mm
Surface of rotor	Uncoated
Material of blades	PA plastic
Material of wall ring	PP plastic
Number of blades	5
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Speed selection max/min - Soft start - Over-temperature protected motor
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	II
Product conforming to standard	EN 60335-1; CE



EC axial fan


sickled blades (S series)
Wall ring with guard grille

Product drawing



- | | |
|---|--|
| 1 | Direction of air flow "V" |
| 2 | Connection line AWG20, 2 x receptacles for tabs 6.3x0.8 mm crimped |


Connection screen



EC axial fan

sickled blades (S series)
Wall ring with guard grille

Charts: Air flow 50 Hz



Measurement: LU-111634

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa
1	230	50	1200	14	0.12	48	56	780	0
2	230	50	1200	16	0.13	48	56	730	7
3	230	50	1200	16	0.13	48	56	665	15
4	230	50	1200	16	0.14	48	56	560	21

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · qv = Air flow
p_{fs} = Pressure increase

