

EC axial fan

sickle-shaped blades (S series)

with round full nozzle

W1G300-DC19-54 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	W1G300-DC19-54	
Motor	M1G074-CF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	1830
Power consumption	W	80
Current draw	A	3.8
Max. back pressure	Pa	100
Max. back pressure	in. wg	0.4
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan

sickle-shaped blades (S series)

with round full nozzle

Technical description


Weight	3.8 kg
Size	300 mm
Motor size	74
Rotor surface	Painted black
Blade material	Press-fitted sheet steel blank, sprayed with PP plastic
Fan housing material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	V
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP42
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	<ul style="list-style-type: none"> - Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Reverse polarity protection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 55022 (Class B)
With cable	Lateral
Protection class assignment	<p>III; Requires supply with safety extra-low voltage SELV.</p> <p>This component for installation may have several local protection classes. This information relates to this component's basic design.</p> <p>The final protection class is based on the component's intended installation and connection. If there is a PE connection point on the housing, it must not be visible after installation.</p>
Conformity with standards	EN 60034-1; EN 60204-1; EN 62368-1
Approval	CSA C22.2 No. 100; EAC; UL 1004-1



EC axial fan

sickle-shaped blades (S series)
with round full nozzle

Product drawing




1	Direction of air flow "V"
2	Cable PVC AWG20
	4x splice



EC axial fan

sickle-shaped blades (S series)
with round full nozzle

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
1	1	Un +24V	red	Power supply 24 VDC, maximum ripple 3.5%
1	2	PWM / lin	yellow	PWM / lin., control input, 0-10 V
1	3	Tach	white	Tach output, 3 pulses per revolution, Isink max = 10 mA
1	4	GND	blue	Reference ground



EC axial fan

sickle-shaped blades (S series)
with round full nozzle

Curves: Air performance



Measurement: LU-114664-1
Measurement: LU-114661-1
Measurement: LU-114665-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	P _{fs}	q _v	P _{fs}
	V	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	28	1965	102	4.11	61	69	2505	0	1475	0.00
2	28	1855	105	4.31	60	67	1975	51	1160	0.20
3	28	1805	107	4.42	59	67	1660	81	975	0.33
4	28	1745	109	4.56	63	71	1330	103	785	0.41
5	24	1810	80	3.80	60	67	2320	0	1365	0.00
6	24	1730	86	4.03	58	67	1845	45	1085	0.18
7	24	1690	87	4.10	57	66	1555	70	915	0.28
8	24	1635	89	4.21	62	70	1245	90	735	0.36
9	16	1380	37	2.63	52	60	1760	0	1035	0.00
10	16	1330	40	2.82	51	58	1410	26	830	0.10
11	16	1305	41	2.92	51	59	1195	42	705	0.17
12	16	1280	43	3.04	56	64	965	54	570	0.22

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side · q_v = Air flow
P_{fs} = Pressure increase

