

W1G300-EC24-04

EC axial fan

with brushless DC motor

Automotive



W1G300-EC24-04 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Muldingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Muldingen GmbH · Headquarters Muldingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	W1G300-EC24-04	
Motor	M1G074-CF	
Nominal voltage	VDC	26
Nominal voltage range	VDC	18 .. 32
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	3000
Power consumption	W	225
Current draw	A	8.5
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	70
-with power derating to	°C	85

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	40.3	29.9
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		50.5	40
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_e	kW	0.24
09 Air flow q_v	m ³ /h	1605
09 Pressure increase p_{fs}	Pa	200
10 Speed (rpm) n	min ⁻¹	2910
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-188993



Technical description


Weight	2.6 kg
Size	300 mm
Motor size	74
Electronics housing material	Die-cast aluminum, painted black
Impeller material	PP plastic
Housing material	Die-cast aluminum
Fan housing material	PP plastic
Number of blades	5
Motor suspension	Motor vibration-damped on both sides
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	Motor IP24 KM, electronics IP6K9K
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H4
Ambient temperature note	Above +70°C with power derating; External sources of heat above 85°C can affect the service life
Max. permitted ambient temp. for motor (transport/storage)	+90 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Cooling hole/opening	On rotor side
Mode	S1
Motor bearing	Ball bearing; (sealed)
Technical features	<ul style="list-style-type: none"> - Start at 85 °C (2 min) permitted - Motor current limitation - Soft start - Control input 0-10 VDC - Temperature derating - Thermal overload protection for electronics
Electrical hookup	Integrated connector (pluggable directly on fan)
Motor protection	Locked-rotor protection
Approval	EAC

EC axial fan

with brushless DC motor

Automotive

Product drawing



1	Airflow direction "V"
2	on both sides for screws for fastening plastics, Ø 3.5 mm
3	Plug TE MCP 2.8, 3-pole, coded
3.1	+ UN
3.2	0-10 V
3.3	GND
Cable 02020-4-1021 with mating connector not included in scope of delivery	
Mating connector comprising housing: TE MCP 2.8: 1-1718627-1, plug contacts: 2.8 mm TE 1241388-1 and TE 1241396-1, seal: 1.2-2.1 mm TE 963294-1 and 2.7-3.0 mm TE 963292-1	




EC axial fan

with brushless DC motor

Automotive


Connection diagram



No.	Conn.	Designation	Function/assignment
	1	UN +24 VDC	Power supply 24 VDC, maximum ripple $\pm 3.5\%$
	2	PWM/LIN	Control input 0-10 V
	3	GND	Reference ground



Curves: Air performance



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-188993-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebmpapst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	26	3000	225	8.50	2755	0	1625	0.00
2	26	2955	251	9.64	2275	100	1340	0.40
3	26	2925	249	9.58	1800	175	1060	0.70
4	26	2850	247	9.48	1310	225	770	0.90
5	26	2680	165	6.32	2455	0	1445	0.00
6	26	2675	182	6.99	2045	81	1205	0.33
7	26	2675	188	7.22	1640	145	965	0.58
8	26	2675	200	7.69	1225	197	720	0.79
9	26	2265	99	3.79	2040	0	1200	0.00
10	26	2255	109	4.17	1705	56	1005	0.22
11	26	2260	112	4.29	1375	102	810	0.41
12	26	2255	118	4.53	1025	137	600	0.55
13	26	1815	53	2.03	1615	0	950	0.00
14	26	1815	58	2.24	1350	35	795	0.14
15	26	1815	60	2.31	1085	64	640	0.26
16	26	1815	63	2.42	815	87	480	0.35

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

